



Oils & Greases

NSF Products

NSF heading



- Safety in the food industry is one of the primary issues faced today
- Minimising risk and ensuring maximum safety are paramount, and lubrication is a key factor
- Few doubt the importance of using food-safe lubricants
- The internationally recognised NSF registration is your guarantee of independent assessment to ensure food quality lubrication
- NSF International took up where the USDA left off; NSF is the only internationally recognised independent authority for the accreditation of food-safe lubricants
- The NSF retained the testing procedures and categories established by the USDA, categorising incidental contact food-safe lubricants as H1
- All NSF registered products are listed on www.nsf.org, so an instant check on the registration status of a product can be made
- All NSF Registered products are also required to carry the NSF 'tick-mark' on the packaging along with the product's registration number

Food Safe Spray

Precision Silicone Spray



- Multi purpose, food grade silicone spray
- For use as an anti-stick film or light lubrication of links, pins, chutes, slides etc
- Light film – does not easily transfer
- Excellent water and chemical resistance
- Long life lubricating film
- Resists oxidation and corrosion
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- Temperature range -50°C to +200°C
- 400ml Aerosol
- NSF H1 registered – 123699

		Price Each	
Order Code	Product Code	1+	6+
WX23063	34035	£12.18	£11.83

Silicone FG



- Excellent versatile lubricant; odourless, colourless, & tasteless
- Lubricates, protects, waterproofs and restores a wide range of parts and equipment
- Highly water-resistant and repels water from treated areas
- Eliminates squeaking, binding and sticking
- Fitted with a 360° spray system for all angle use, even upside down
- Temperature range -40°C to +200°C
- 400ml aerosol
- NSF H1 registered - 138000

		Price Each	
Order Code	Product Code	1+	6+
WX42632	6150009350	£6.30	£5.57

Foodlube Spray



- High performance food grade multi-purpose lubricant aerosol
- Use for all round light to medium lubrication of most moving parts
- Good load carrying properties (180kg weld load)
- Good dewatering properties
- Excellent penetration
- Thin long lasting film
- Excellent corrosion protection
- Temperature range -20°C to +110°C
- 300ml Aerosol
- NSF H1 registered – 121616

		Price Each	
Order Code	Product Code	1+	6+
WX23054	15710	£14.21	£13.80

Foodlube Spray Grease



- Food grade multi-purpose EP grease fortified with PTFE
- Tenacious lubrication of slides, bushes, pins and bearings
- Outstanding EP performance (620kg weld load)
- Highly resistant to water wash-off
- Excellent corrosion protection
- Temperature range -50°C to +160°C
- 400ml Aerosol
- NSF H1 registered – 138048

		Price Each	
Order Code	Product Code	1+	6+
WX38289	15030	£13.30	£12.91

Spray Grease FG



- Multi-purpose grease for the lubrication of a wide variety of parts, hinges, and bearings
- Semi-liquid state upon application allows the grease to penetrate moving parts
- NLGI grade 2 grease in an aerosol
- Good penetration before thickening rapidly
- Good thermal stability: resists steam
- Temperature range -20°C to +140°C (180°C intermittent)
- 400ml aerosol
- NSF H1 registered - 140258

		Price Each	
Order Code	Product Code	1+	6+
WX45531	6150009500	£6.49	£5.73

Foodlube Chain Spray



- Aerosol applied multipurpose chain and conveyor lubricant
- Ideal for the lubrication of all types of chains and conveyors where convenience of aerosol applications is preferred
- Highly resistant to water wash off
- Non-drip tenacious film
- Excellent penetration
- Good load carrying capabilities
- Excellent corrosion protection
- Temperature range -20°C to +150° (180°C for short periods)
- 400ml Aerosol
- NSF H1 registered - 122878

		Price Each	
Order Code	Product Code	1+	6+
WX23053	15610	£20.28	£19.70

Chain Lube FG



- A high performance, foaming, chain lubricant based on stable vegetable oils with added PTFE
- The gentle foaming action ensures excellent penetration and prevents dripping
- Formulated using only food industry acceptable components
- Good adhesion on metal surfaces, even at elevated temperatures and high rpm
- Temperature range -15°C to +175°C
- 400ml aerosol
- NSF H1 registered - 137998

		Price Each	
Order Code	Product Code	1+	6+
WX42633	6150009330	£10.62	£9.38

Foodlube Shock-Release



- Shock-Release rapidly frees fittings, fasteners and mechanical assemblies seized by dirt and corrosion
- Freezing action causes micro-cracking for rapid release
- Shock cooling temperature -40°C
- Advanced synthetic base oils reinforced with sub-micron PTFE
- Safe on metals, common plastics and rubbers
- Low odour
- Released parts protected from corrosion and stay lubricated
- 360° spray valve and mini jet actuator built-in
- 400ml aerosol
- NSF H1 registered - 141594

		Price Each	
Order Code	Product Code	1+	6+
WX45579	32040	£7.13	£6.93

Foodlube Dismantling Spray



- Quick effective release of seized and corroded threaded fasteners
- Excellent penetration of rust, scale and general grime
- Protective film provides short term corrosion protection
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- Temperature range -20°C to +110°C
- 300ml Aerosol
- NSF H1 registered - 121617

Price Each

Order Code	Product Code	1+	6+
WX38290	15720	£15.94	£15.48

Foodlube WD Spray



- Highly effective water displacing spray
- Leaves a light lubricating and anti-corrosive film that protects all metal parts
- Can be used to maintain and protect parts after washing
- Good load carrying capability
- Long life lubricating film, with PTFE
- Temperature range -20°C to +150°C
- 300ml Aerosol
- NSF H1 registered - 136265

Price Each

Order Code	Product Code	1+	6+
WX33912	15010	£14.64	£14.22

Moisture Remover FG



- NSF registered dewatering fluid
- Quickly drives out moisture from equipment and electronics
- Ideal for use as a light, multi-purpose lubricant
- Excellent materials compatibility
- Can be used as a penetrating oil
- Equipped with 360° (spray system) valve for all angle use
- Heat Resistance : 120°C (150°C short time)
- 500ml aerosol
- NSF H2 registered - 142200

Price Each

Order Code	Product Code	Size	1+	6+
WX52484	6150009530	400ml	£4.45	£3.93

Foodlube Multi-Lube



- Food grade multi-purpose penetrating lubricant fortified with PTFE
- Ideal for use on chains, bearings & slides in food/clean environments
- Good load carrying properties
- Good dewatering properties
- Excellent penetration
- Excellent corrosion protection
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- Temperature range -50°C to +180°C
- NSF H1 registered - 127935

Price Each

Order Code	Product Code	Size	1+	6+
WX38293	15120	500 ml Trigger Spray	£23.40	£22.77
WX38294	15126	5 Ltr	£121.21	£117.93

Machine Oil FG



- Exhibits excellent penetrating ability and loosens rust, scale, dirt and corrosion to free parts and fasteners
- Does not resinify, allowing longer lubrication intervals
- Creates an effective water-repellent film
- Safe for use on metals, most plastics, painted surfaces and wood
- 400ml aerosol fitted with a 360° Spray System for all angle use, even upside down
- Temperature range -18°C to +120°C (150°C short time)
- NSF H1 registered: Aerosol - 137999
- NSF H1 registered: Bulk - 140249

Price Each

Order Code	Product Code	Size	1+	6+
WX42634	6150009340	400ml	£7.74	£6.83
WX45529	6150009460	5 Ltr	£49.83	£44.02

Foodlube Dry PTFE



- Multi-purpose, food grade PTFE aerosol for light lubrication
- Use as a dry anti-stick film or light lubrication of links, pins, chutes, slides etc
- Insoluble in water and solvents
- Light film – does not easily transfer
- Effective anti-stick properties
- Clean, dry, non-toxic, colourless film
- Temperature range -200°C to +270°C
- 400ml Aerosol
- NSF H1 registered - 123703

Price Each

Order Code	Product Code	Size	1+	6+
WX23067	34235		£15.70	£15.25

Dry PTFE Lube FG



- Forms an opaque, clean, dry film with effective anti-stick properties
- Non-toxic colourless film for the light lubrication of chutes, slides, pins etc
- Low environmental dust/dirt adherence
- Good resistance to water, oils and solvents
- Resists wash-off by pressure cleaners
- Particularly suitable in low load, low speed applications
- Temperature range -150°C to +260°C
- 400ml aerosol
- NSF H1 registered - 139899

Price Each

Order Code	Product Code	1+	6+
WX45532	6150009520	£7.11	£6.28

Food Safe Grease

Foodlube PUROL



- NEW NSF H1 and 3H Grease
- PUROL™ is a multi-purpose grease for incidental food contact and a food processing release agent for direct food contact
- PUROL is suitable for seals, mincer plates, mixers and slicers where food contact cannot be avoided
- PUROL offers a wide temperature range -10°C to +110°C
- NSF registered - 143392

Price Each

Order Code	Product Code	Size	1+	4+
WX52488	15611	370g Cartridge	£21.70	£21.07
WX52489 ‡	15616	4kg	£150.32	£146.26

‡ Special delivery applies. Please call for details

Easy ordering by phone, fax, email, web or via your local Brammer Sales and Service Centre

Foodlube Premier



- Triple life grease with extended relubrication intervals
- A high performance EP grease, fortified with PTFE
- Significantly extends bearing life
- High load and wear properties
- Highly resistant to water wash off
- Excellent corrosion protection
- High speed applications
- Temperature range -30°C to +180°C
- Wide range of applications including; fans & hotter running applications, high temperature oven bearings and electric motors

NLGI No 00

- NSF H1 registered – 141083

Order Code	Product Code	Size	Price Each	
			1+	4+
WX42635 ‡	15266	4Kg	£148.17	£144.16
WX42636 ‡	15264	18Kg	£626.74	£609.80

NLGI No 1

- NSF H1 registered – 141084

Order Code	Product Code	Size	Price Each	
			1+	4+
WX42637	15291	380g	£19.43	£18.87
WX42638	15296	4Kg	£148.17	£144.16
WX42639 ‡	15294	18Kg	£626.74	£609.80

NLGI No 2

- NSF H1 registered – 141082

Order Code	Product Code	Size	Price Each	
			1+	4+
WX42642	15311	380g	£19.43	£18.87
WX42643	15316	4Kg	£148.17	£144.16
WX45572 ‡	15314	18Kg	£626.74	£609.80

‡ Special delivery applies. Please call for details

Foodlube Universal Greases



- Designed for effective lubrication of all types of ball, roller and plain bearings operating under high loads in the food and other clean industries
- Suitable multi-purpose applications and those operating at low or high temperatures, high loads and those which require high water resistance
- Fortified with PTFE
- Available in NLGI ISO 000, 0 and No 2
- Designed for use in centralised, multi-line lubrication systems
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- Temperature range -50°C to +160°C

NLGI No 000

- NSF H1 registered – 122068

Price Each

Order Code	Product Code	Size	1+	4+
WX23050	15286	4Kg	£151.81	£147.70
WX23052	15284	18Kg	£681.15	£662.74

NLGI No 0

- NSF H1 registered – 122067

Price Each

Order Code	Product Code	Size	1+	4+
WX23047	15276	4Kg	£148.17	£144.16
WX23049	15274	18Kg	£626.74	£609.80

NLGI No 2

- NSF H1 registered – 121603

Price Each

Order Code	Product Code	Size	1+	4+
WX23043	15231	380g Cartridge	£19.43	£18.87
WX23044	15236	4kg	£148.17	£144.16
WX23046	15234	18kg	£626.74	£609.80

Ambergrease FG3



- Multi-purpose bearing grease for longterm lubrication
- Resistant to water and steam
- Protects against corrosion
- Translucent Aluminium-Complex, NLGI 2
- Temperature range -20°C to +140°C (180°C intermittent)
- NSF H1 Registered - 140248

Price Each

Order Code	Product Code	1+	6+
WX45530	6150009490	£8.45	£7.47

Molykote Synthetic Grease



- Multi-purpose white PAO synthetic grease
- Aluminium complex thickener fortified with PTFE
- Provides high load carrying capacity
- High wear resistance and long service life
- Excellent low temperature torque
- Good compatibility with most substrates including many plastic and rubber materials
- Temperature range -40°C to +150°C
- NSF H1 registered - 127847

Price Each

Order Code	Product Code	Size	1+	6+
WX34072	G4500X400GRM	400g Cartridge	£16.00	£14.67
WX34073	G4500X5KG	5 Kg	£148.20	£135.85

Ambergrease FG1



- Excellent in extremes of temperature, wet and saturated environments, and heavily loaded applications
- Contains Extreme Pressure additives and PTFE to provide a high degree of anti-wear performance
- White tacky grease, NLGI 2
- Suitable for all plain and anti-friction bearings as well as sliding surfaces
- Extends lubrication intervals & working life of components
- Temperature range -50°C to +165°C
- 400g cartridge
- NSF H1 Registered - 138264

Price Each

Order Code	Product Code	1+	6+
WX42644	6150009370	£12.00	£10.60

Foodlube High Temp 2



- A semi-translucent NLGI No 2 silicone grease fortified with PTFE
- Suitable for lubrication of all types of slower bearings and sliding surface operating at high temperatures
- Mineral hydrocarbons free
- Resistant to caustic washing
- Temperature range -20°C to +200°C
- NSF H1 registered – 122065

Price Each

Order Code	Product Code	Size	1+	4+
WX23029	15251	380g Cartridge	£34.60	£33.66
WX23030 ‡	15256	4kg	£256.54	£249.61
WX33110 ‡	15254	18kg	£1046.32	£1018.04

Ambergrease FG2



- High temperature NLGI 2 white semi-translucent grease
- PTFE solid lubricant improves anti-wear performance prolonging component life
- Suitable for all plain and anti-friction bearings as well as sliding surfaces
- Reduces carbonisation often found in high temperature grease
- Temperature range -20°C to +220°C
- 400g cartridge
- NSF H1 registered - 138265

Price Each

Order Code	Product Code	1+	6+
WX42645	6150009380	£20.09	£17.75

Foodlube Extreme



- Food grade bearing grease with superior performance in wet conditions for the lubrication of all types of plain, roller & ball bearings in the food & other clean industries
- Significantly extends bearing life
- Superior resistance to water washout
- Excellent corrosion protection
- NLGI 2
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- Temperature range -30°C to +160°C
- NSF H1 registered – 132235

Price Each

Order Code	Product Code	Size	1+	4+
WX33111	15241	380gm	£19.43	£18.87
WX33112	15246	4 Kg	£148.17	£144.16
WX33113 ‡	15244	18 Kg	£626.74	£609.80

Sapphire Endure



- Sapphire Endure is a PFPE (Perfluorinated polyether) long life grease fortified with PTFE
- Extremely stable at high temperatures
- Resistant to chemical and solvents in aggressive environments
- Excellent anti-wear properties
- Greatly extended lubrication intervals
- NLGI 2
- Temperature range -25°C to +280°C
- NSF H1 registered – 123718

Price Each

Order Code	Product Code	Size	1+	4+
WX34061	12330	100g Tube	£88.96	£86.55
WX34062	12331	700g Cartridge	£582.31	£566.57
WX34063 ‡	12334	1 Kg	£810.29	£788.39

‡ Special delivery applies. Please call for details

For condition monitoring, see our Test & Measurement section



Foodlube Multi-Paste



- Multipurpose smooth white anti-seize and lubricating paste
- For use as an anti-seize/assembly paste, lubricating bushes, slides and small open gears
- Ideal for stainless steel fasteners, particularly at elevated temperatures
- Extremely low sulphur & chlorine levels
- Extremely tenacious – resists water wash off
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- Temperature range -30°C to +450°C

Multi-Paste

- NSF H1 registered - 121614

Price Each

Order Code	Product Code	Size	1+	4+
WX23033	15750	85g	£13.74	£13.36
WX42646	15851	400g	£19.18	£18.66
WX23034	15753	500g	£27.93	£27.18
WX23035	15756	20 Ltr	£256.39	£249.46

Multi-Paste Spray

- NSF H1 registered – 121613

Price Each

Order Code	Product Code	Size	1+	6+
WX42647	15751	400ml Aerosol	£16.37	£15.90

Assembly Paste FG



- Assists Assembly of Components
- Tenacious white paste formulated to reduce wear to moving components during the running-in period
- High solids content which provides instant lubrication to bearings and sliding surfaces whilst the bearing grease is worked to release its lubricating oils
- Compatible with most grease types
- Temperature range; -30°C to +150°C as a lubricant and up to +1100°C as an anti-seize
- 400ml Aerosol
- NSF H1 registered - 139900

Price Each

Order Code	Product Code	1+	6+
WX42648	6150009400	£8.72	£7.70

Loctite 8104



- Food grade colourless silicone grease
- Recommended for lubrication of most elastomeric and plastic parts
- Food approved, meets CNERNA Guide 1992
- Temperature range -50°C to +200°C
- H1 NSF Reg No: 122981

Price Each

Order Code	Product Code	1+	3+
WX25447	8104X75ML	£9.84	£9.46
WX25446	8104X1LTR	£48.26	£46.40

Food Safe Oils

Foodlube Hi Torque



- Food-safe gearbox fluids incorporating SuPs to provide maximum protection on start up
- Synthetic food-safe formulation
- Excellent load carrying: FZG load stage 12
- Highly resistant to water wash off
- Increased service intervals
- Excellent corrosion protection
- Temperature range -20°C to +150°C
- 320/460 grade ideal for high temperature chains up to 180°C

Hi Torque 150

- NSF H1 registered – 121604

Price Each

Order Code	Product Code	Size	1+	4+
WX33913	15426	5 Ltr	£129.11	£125.62
WX33914	15425	20 Ltr	£448.10	£435.99

Hi Torque 220

- NSF H1 registered – 122073

Price Each

Order Code	Product Code	Size	1+	4+
WX33915	15526	5 Ltr	£129.11	£125.62
WX33916	15525	20 Ltr	£448.10	£435.99

Hi Torque 320

- NSF H1 registered – 122072

Price Each

Order Code	Product Code	Size	1+	4+
WX33917	15766	5 Ltr	£129.11	£125.62
WX38295	15765	20 Ltr	£448.10	£435.99

Hi Torque 460

- NSF H1 registered – 122071

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33919	15776	5 Ltr	£129.11	£125.62
WX33920	15775	20 Ltr	£448.10	£435.99

Rapid Demulse



- High performance oil formulated to maximise lubricant lifetime, even under conditions of high load and elevated temperature
- Rapid Demulse 220 has excellent demulsification properties for rapid separation of water which is particularly useful when used with water cooled homogenisers and similar systems
- Temperature range -5°C to 130°C
- Excellent water demulsification
- Good wear protection properties
- Does not contain: mineral hydrocarbons, animal derived materials, nut oils or genetically modified ingredients
- NSF H1 registered – 140252
- For optimum performance, drain and flush prior to filling with Rapid Demulse 220

Order Code	Product Code	Size	Price Each	
			1+	4+
WX42649	15965	20 Ltr	£256.94	£250.00
WX42650 ‡	15969	200 Ltr	£2234.69	£2174.30

‡ Special delivery applies. Please call for details

Foodlube Hi Power



- Uniquely suitable for use in hydraulics and compressors, the Hi Power range is food safe and premium quality
- Fully synthetic food safe range
- For use in compressors, hydraulics and airline systems
- Does not form deposits, sludge or varnish
- Increased oxidation resistance
- Excellent corrosion protection
- Very low foaming
- L-CO; unique low carry over system to enhance compressor performance
- High thermal stability
- Temperature range -20°C to +100°C
- Can be used down to -50°C depending on viscosity grade and application

Hi Power 22

- NSF H1 registered - 122180

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33921	15796	5 Ltr	£129.11	£125.62
WX33922	15795	20 Ltr	£448.10	£435.99

Hi Power 32

- NSF H1 registered - 122181

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33923	15896	5 Ltr	£129.11	£125.62
WX33924	15895	20 Ltr	£448.10	£435.99

Hi Power 46

- NSF H1 registered - 122182

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33925	15996	5 Ltr	£129.11	£125.62
WX33926	15995	20 Ltr	£448.10	£435.99

Hi Power 68

- NSF H1 registered - 122183

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33927	16006	5 Ltr	£129.11	£125.62
WX33928	16005	20 Ltr	£448.10	£435.99

Hi Power 100

- NSF H1 registered - 122184

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33929	15946	5 Ltr	£129.11	£125.62
WX33930	15945	20 Ltr	£448.10	£435.99

Foodlube Vac Pump Oil



- High performance vacuum oil formulated to maximise lubricant lifetime, even under conditions of high load and elevated temperature
- Low vapour pressure to enhance pump efficiency and is suitable for use with a wide range of vacuum pump formats
- Temperature range -5°C to 130°C
- Minimises deposits in vacuum pump systems
- Clean, low odour product
- Prevents corrosion from moisture ingress
- Does not contain: animal derived materials, nut oils or genetically modified ingredients
- NSF H1 registered - 137855
- For optimum performance, drain and flush prior to filling with Rocol Vac Pump Oil

Order Code	Product Code	Size	Price Each	
			1+	4+
WX38296	16806	5 Ltr	£80.39	£78.22
WX38297	16805	20 Ltr	£230.61	£224.38

Food Safe Chain Lubricants

Foodlube Chain Fluid



- Suitable for all types of chain and conveyor drive chains
- Food safe for all transport areas
- Excellent corrosion protection
- Good load carrying capacity
- Superior resistance to water wash-off
- Temperature range -20°C to +150°C (180°C for short periods)
- NSF H1 registered - 122069

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33931	15506	5 Ltr	£130.33	£126.81
WX33932	15505	20 Ltr	£467.92	£455.27

Foodlube Overhead Chain Fluid



- Similar to FOODLUBE Chain Fluid but specifically formulated for overhead chains
- Non-drip tenacious film
- Highly resistant to water wash-off
- Excellent corrosion protection
- Excellent penetration
- Good load carrying capabilities
- Good water displacing properties
- Temperature range -20°C to +150°C
- NSF H1 registered - 123859

Order Code	Product Code	Size	Price Each	
			1+	4+
WX33933	15786	5 Ltr	£130.33	£126.81
WX33934	15785	20 Ltr	£467.92	£455.27

Personal protection equipment, see our Personal Protection Equipment section



Bakerlube™ CL



- High temperature, long life, synthetic EP chain and conveyor lubricant
- Specially formulated for the lubrication of conveyor chains and bearings operating at temperatures up to 280°C
- Particularly suitable for stenters, drying machines, kilns, bakery ovens and other similar applications
- Outstanding anti-wear performance
- Solvent free formulation
- Excellent penetration
- Clean, residue free film
- Does not contain solvents
- Suitable for automatic lubricators
- Long wet film life at high temperatures provides long term lubrication
- Temperature range 0°C to +280°C
- NSF H2 Registered - 141864

Price Each

Order Code	Product Code	Size	1+	4+
WX45573 ‡	15605	20 Ltr	£328.29	£319.42

‡ Special delivery applies. Please call for details

Bakerlube™ HT



- Extreme high temperature, graphited chain and conveyor lubricant
- Specifically designed as a high quality, dry film lubricant for conveyor chains and bearings in high temperature bakery ovens
- It is ideally suited for use where temperatures are too high for wet lubricants to be used
- Temperature range: moist film -10°C to +180°C
- Dry film protection up to +550°C
- Good EP and anti-wear performance
- High load carrying performance
- Clean evaporating base oil
- For temperatures where conventional fluids fail
- Contains fine particles of high purity graphite for excellent penetration and performance
- Does not contain solvents
- Dry film (above 180°C) - Does not attract dust/dirt
- Excellent penetration (must be applied below 120°C)
- NSF H2 Registered - 141863

Price Each

Order Code	Product Code	Size	1+	4+
WX45574 ‡	15705	20 Ltr	£297.61	£289.57

‡ Special delivery applies. Please call for details

Aerosol Lubricants

PTFE Lubricants

Dry Film Anti-Stick



- Forms a dry PTFE based non-staining film
- Suitable where the use of wet or silicone lubricants is undesirable
- Exhibits excellent friction retardant properties
- Suitable as an anti-tracking agent
- Wide operational temperature range -100°C to +200°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX38303	6140003500	£11.62	£10.27

Triflow™



- Triflow - Superior lubricant with micronized Teflon(F)
- Virtually eliminates friction and wear, even under the most extreme pressure and abrasive conditions
- Displaces and prevents the build-up of dirt and dust
- Repels moisture, preventing the formulation of ice, rust and other corrosives
- Effective at -53°C to +246°C
- Lubricates
- Penetrates
- Protects

Price Each

Order Code	Product Code	1+	4+
WX23169	TRIFLOWX200ML	£13.40	£11.80
WX23170	TRIFLOWX500ML	£23.30	£20.50
WX23171	TRIFLOWX4LTR	£142.00	£124.00

Sapphire Precision Lube



- Ultra high performance maintenance lubricant with PTFE
- Outstanding EP performance (315kg weld load)
- Provides excellent lubrication, penetration and protection in the widest range of applications
- Clean non-toxic lubricating film
- Free from chlorinated solvents
- Can be sprayed from any angle due to 360° valve technology, enabling easy application of the product
- Temperature range -50°C to +250°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23070	34341	£14.00	£13.59

Blue Works Multi-purpose



- Multi-purpose synthetic lubricant with PTFE
- Very low surface tension for excellent penetration
- Penetrates to loosen stuck parts
- Drives out moisture and stops corrosion
- Leaves a thin, clear protective film
- Removes light soils and contaminants
- Effective performance at temperatures from -20°C to +100°C
- NSF H2 Registered No 143811
- 400ml aerosol

Price Each

Order Code	Product Code	1+	12+
WX52490	44420	£6.09	£5.78

Blue Works Dry Lube PTFE



- Quick-drying PTFE formula
- Superior lubrication and long-lasting corrosion protection
- No oily residue
- Reduces friction and wear
- Resists dirt, dust and oil
- Wide operating temperature range
- Effective performance at temperatures from -20°C to +250°C
- Safe to use on wood, paper, glass, leather, metal and most plastics
- NSF H2 Registered No 143809
- 400ml aerosol

Price Each

Order Code	Product Code	1+	12+
WX52491	44425	£5.45	£5.17

Blue Works High Performance PTFE



- Quick-drying PTFE formula
- Provides maximum protection under extreme temperature, pressure and motion
- Long-lasting lubrication and corrosion protection
- Excellent for heavy load applications
- Safe for use on all metal and most non metal surfaces including glass, vinyl, rubber and most plastics
- Effective performance at temperatures from -20°C to +100°C
- NSF H2 Registered No 143812
- 400ml aerosol

Price Each

Order Code	Product Code	1+	12+
WX52492	44421	£6.09	£5.78

White Grease with PTFE



- Water resistant white grease with PTFE
- Suitable for a wide range of anti-friction situations
- Drop Point greater than +140°C
- 400ml aerosol

Order Code	Product Code	Price Each	
		1+	6+
WX38304	R223	£3.67	£3.29

MECRO PTFE Plus



MECRO

- Penetrates, lubricates, protects
- Eliminates moisture, corrosion and electrical shorting
- 600ml aerosol

Order Code	Product Code	Price Each	
		1+	6+
WX45562	PTFE-PLUS-600	£4.85	£4.34

MECRO White Grease & PTFE



MECRO

- Scientifically prepared grease
- Formulated to resist heat and water and also protect against corrosion
- Use on hinges, gears, bearings, springs, 'o' rings, sliding shackles and striker plates
- 600ml aerosol

Order Code	Product Code	Price Each	
		1+	6+
WX45564	PTFE-WHITE-600	£5.04	£4.52

MECRO Silicone & PTFE



MECRO

- 100% active stainless and odourless polysiloxane lubricating and releasing agent
- Designed to prevent rust, corrosion and sticking on a wide variety of materials
- 600ml aerosol

Order Code	Product Code	Price Each	
		1+	6+
WX45563	PTFE-SILICONE-600	£4.96	£4.45

Dry Moly Lubricants

Rocol Dry Moly Lube



- Dry film lubrication - resists pick up of contaminants
- Developed to lubricate sliding mechanisms such as plain bearings, pins, cams and slides where a wet lubricant cannot be tolerated
- Prevents galling, pick up and seizure
- Excellent wear resistance (high molybdenum disulphide content)
- Temperature range of applied film -200°C to +450°C
- 400ml Aerosol

Order Code	Product Code	Price Each	
		1+	4+
WX23001	10025	£33.06	£32.10

Molykote 321R



- Molybdenum disulphide (MoS₂) based lubricant
- Air curing dry film lubricant, dries in 5 minutes at 20°C
- Metal/metal combinations with slow to medium fast movements and high loads
- Permanent lubrication of highly stressed slideways etc
- Avoidance of stick slip
- Temperature range -180°C to +450°C

Order Code	Product Code	Size	Price Each	
			1+	6+
WX33943	D321RX400ML	400ml Aerosol	£14.66	£13.44
WX33944	D321RX1KG	1 Kg	£75.96	£69.63
WX33945 ‡	D321RX5KG	5 Kg	£372.02	£341.02

‡ Special delivery applies. Please call for details

Dry Moly Spray



Ambersil

- Dry Molybdenum Disulphide (MoS₂) lubricant
- Resin bonded, high pressure / load resistant, dry film lubricant
- Ideal for metal-to-metal lubrication where a wet film cannot be tolerated
- Tough and long lasting
- Dry film will not attract dust, dirt or contaminants and repels water
- Assists assembly and running-in
- Wide temperature range: -150°C to +400°C
- 400ml aerosol

Order Code	Product Code	Price Each	
		1+	6+
WX42651	6150002000	£10.83	£9.57

Silicone Lubricants

Silicone Spray



Ambersil

NEW

- General purpose silicone lubricant
- Provides good slip on blades, slides and chutes
- WRAS approved for use in water industry
- Odourless & colourless
- Temperature range -50°C to +200°C
- 500ml aerosol

Order Code	Product Code	Price Each	
		1+	6+
WX52485	6190015000	£3.25	£2.87

MECRO Silicone Spray FG



MECRO

- Dry silicone lubricant and mould release capable of easing friction between surfaces
- Provides invisible lubrication properties giving protection with a touch free finish
- For use in injection moulding as a release agent
- For areas where incidental contact with food may be expected
- It is not intended to be a direct lubricant for food
- 600ml aerosol

Order Code	Product Code	Price Each	
		1+	6+
WX45556	F/G-SILICONE-600	£4.19	£3.76

Blue Works Silicone



- Quick drying no-mess silicone
- Withstands high temperature and high pressures
- Excellent lubrication on metal, plastic and rubber material
- Lubricates, waterproofs and protects
- Eliminates sticking and binding, stops squeaks
- Effective performance at temperatures from -35°C to +200°C
- NSF H2 Registered No 143770
- 400ml aerosol

Price Each

Order Code	Product Code	1+	12+
WX52493	44419	£5.82	£5.52

3-IN-ONE Range

3-IN-ONE



- Lubricating, cleaning and protecting since 1894
- Silicone free light oil for general purpose use
- Lubricates, cleans and prevents rust
- 3-IN-ONE with PTFE for added wear resistance, longer lifespan and low friction

Price Each

Order Code	Product Code	Type	1+	4+
WX23198	3IN1X100ML	Flexi Drip Can	£1.85	£1.76
WX23200	3IN1X200ML	Flexi Drip Can	£3.02	£2.86
WX40379	3IN1-AERO-200ML	Aerosol	£2.29	£2.17
WX23197	3IN1-PTFEX250ML	Aerosol	£2.60	£2.47

3-IN-ONE Professional



- 3-IN-ONE professional range comprises uniquely formulated products
- The latest developments from 3-IN-ONE formulated to meet the toughest demands

Product

Benefits

- High Performance Lubricant
- Outstanding long-lasting lubricant with PTFE
 - Prevents corrosion
 - Drives out moisture
 - Safe on metal, wood, vinyls and most plastics

Anti-Seize Copper Grease

- Powerful lubricant and anti-seize compound
- Protects metal from corrosion, water, heat and acid
- Withstands temperatures of -30°C to +1100°C

Silicone Spray Lubricant

- Long-lasting, quick drying lubricant
- Versatile, 'go-anywhere' product
- Safe to use on metal, rubber, wood and vinyl

White Lithium Grease

- Heavy duty, long-lasting lubricant
- Prevents rust and corrosion
- Heat and water resistant
- Will not splatter, melt or wash-off

Penetrant Spray

- Fast-acting lubricant
- Loosens seized parts
- Frees rusted nuts and bolts

Price Each

Order Code	Product Code	1+	4+
WX40380	3IN1-HPLX400ML	£5.58	£5.29
WX40381	3IN1-ASCGX300ML	£4.24	£4.02
WX30004	3IN1-SILICONEX400ML	£4.00	£3.79
WX30005	3IN1-WHT-LITHIUMX400ML	£3.96	£3.76
WX30003	3IN1-PENETRANTX400ML	£4.62	£4.38

WD-40 Range

WD-40



- Multi-purpose maintenance lubricant
- Disperses moisture, eliminates water-induced short circuits
- Penetrates rust through to metal and stuck parts
- Lubricates and stops squeaks
- Inhibits corrosion with a protective barrier
- Cleans dirt, grime, caked grease and oil
- Contains no silicone or other additives that attract dust and dirt

Price Each

Order Code	Product Code	1+	4+
WX23202	WD40X100ML	£1.76	£1.67
WX23204	WD40X250ML	£2.80	£2.66
WX23206	WD40X450ML	£4.22	£4.00
WX23208	WD40X600ML	£5.24	£4.97
WX23207	WD40X5LTR+APPLIC	£23.65	£22.43
WX33935 ‡	WD40X200LTR	£693.75	£657.86
WX23201	WD40-APPLICATORSPRAY	£3.75	£3.55

‡ Special delivery applies. Please call for details

WD-40 Smart Straw



- Dual-action spray adds outstanding versatility and performance to an established product
- Quick, economical and simple one-hand action
- Flip up for precision spray, flip down to spray large areas
- Spray mechanism permanently attached, no more lost straws!
- 420ml aerosol

Price Each

Order Code	Product Code	1+	4+
WX40385	WD40X420ML	£4.16	£3.95

Penetrant Spray

Blue Works Penetrant



- Frees stuck and corroded parts
- Inhibits rust from coming back
- Capillary action quickly penetrates into tight crevices, threads and seams
- Lubricates and prevents rust and corrosion
- 400ml aerosol

Price Each

Order Code	Product Code	1+	12+
WX52494	44418	£5.82	£5.52

Loctite 8040



- Releases seized and corroded parts
- Frees by shock freezing (-43°C)
- Provokes differential thermal contraction of the parts due to the abrupt chill-down
- Dismantle after allowing 1 - 2 minutes reaction time
- Fast and efficient wicking of the lubricating ingredient
- Released parts remain lubricated and protected from corrosion

Price Each

Order Code	Product Code	1+	3+
WX38298	8040X400ML	£5.96	£5.90

Rust Flash



Ambersil

- Fractures the layer of rust and dirt by delivering a thermal shock (down to -40°C)
- Allows the active lubricating ingredients to penetrate quickly and deeply
- Frees metal parts seized by dirt, rust, corrosion or dried-up greasy deposits
- Ensures quick disassembly of; mechanical components, fittings, assemblies, nuts, bolts and other close tolerance fasteners
- Reduces maintenance costs through time saving
- Reduces scrap rate of seized parts
- Does not contain silicones
- Safe for all metals and for most plastics and rubbers
- Fitted with the 360° spray system for all angle use
- 500ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX40378	6150003601	£4.79	£4.23

Penetrating Oil



Ambersil

- High-grade lubricating agent based on a mixture of oils and penetrants in a blend of solvents
- Ideal for freeing nuts, bolts, screws, studs, pins, valves, machine parts, pipe couplings and pulleys
- Can also be used for cleaning rusted surfaces of moulds, dies and heavy tools and for softening or removing carbon deposits
- Frees seized components rapidly and will lubricate and protect against further corrosion
- Penetrates deeply and deposits a specialised corrosion inhibiting lubricant to facilitate re-assembly
- Contains MoS₂
- Will not damage metals, alloys, paint, rubber, plastic or wood
- 400 ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45528	6150003600	£5.06	£4.47

Contact Duck Oil



Contact Brammer on 0870 240 2100



- Multi-purpose service spray
- Displaces water - ideal for removing moisture from electrical appliances
- Protects electrical contacts
- Non-conductive - high dielectric strength
- Prevents corrosion, penetrates and releases
- Stops moisture, releases frozen nuts and lubricates mechanical and electrical systems
- Silicone free
- High flash point - low fire hazard, can be used in most situations
- Film forming - good protection against corrosion
- 5Ltr comes with an empty trigger spray bottle

Price Each

Order Code	Product Code	Size	1+	4+
WX45538	SD0500ML	500ml Aerosol	£5.05	£4.80
WX45539	SD05L	5 ltr Bulk	£29.95	£29.00
WX45537 ‡	SD025L	25 ltr Bulk	£125.00	£120.50

‡ Special delivery applies. Please call for details

Rocol Penetrating Spray



- Powerful penetrating fluid, with molybdenum disulphide, in an aerosol
- Excellent penetrating of rust, scale, grease, dirt etc
- Molybdenum disulphide aids dismantling
- Corrosion inhibitors to provide a protective film against further corrosive attack
- Fast acting performance
- Carbon dioxide propellant
- 300ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23028	14021	£12.10	£11.75

PlusGas Dismantling Lubricant



- PlusGas Formula 'A' dismantling fluid for de-seizing all corroded metal parts
- Penetrates deep down to break the grip of rust, scale, carbon, paint or gum
- Lubricates threaded components to aid re-assembly
- Helps prevent corrosion and displaces moisture

Price Each

Order Code	Product Code	Size	1+	6+
WX33936	07660704893	200ml Aerosol	£3.89	£3.63
WX33937	07660704894	400ml Aerosol	£6.11	£5.73
WX33938	07660704897	250ml Tin with spout	£3.57	£3.35
WX33939	07660704895	500ml Tin with spout	£5.95	£5.56
WX33940	07660704896	1 Litre Tin	£9.80	£9.18
WX33941	07660704898	5 Litre Tin	£34.27	£32.11

40+



Ambersil

- Quickly frees seized nuts, bolts and bearings
- Remains operational at sub-zero temperatures
- High corrosion protection and water displacement properties - Passes IP 178, Methods A and B
- Non-conductive film
- Safe on most paints, rubbers and plastics
- Rolls Royce Aerospace approved 1036J
- Treated metals resist finger printing and remain bright even in highly corrosive conditions
- Aerosol has a convenient 360° (all angle) spray system

Price Each

Order Code	Product Code	Size	1+	6+
WX38299	6130007000	400ml aerosol	£3.62	£3.20
WX45533	6230005100	5 ltr	£20.92	£18.48
WX45534 ‡	6230006100	25 ltr	£71.11	£62.82
WX45535 ‡	6230008100	200 ltr	£483.45	£427.05

‡ Special delivery applies. Please call for details

My CRC - an Ambersil service



Ambersil

- My CRC - an Ambersil service giving you automatic datasheet updating
- The original datasheet updating service for MRO chemicals
- 100% confidence that your chemical datasheets are current
- 24/7 access to all datasheets
- Simple registration at www.ambersil.com
- Select the products used, to automatically be notified of changes to TDS and MSDS
- Multiple email addresses to keep key personnel updated

PX24



Ambersil

- Multi-purpose protective fluid, corrosion inhibitor, dewatering fluid and lubricant
- Water displacement - complete displacement of NaCl test solution (IP 178)
- Corrosion protection - pass/no corrosion (IP178)
- Copper corrosion - IP 154 max 1; no pitting or etching
- No adverse effects on rubber, plain-work or plastics and acrylic sheet, polyester, glass fibre laminate, vinyl sheet and ebonite after immersion for 240 hours
- Temperature range -20°C to +115°C
- Convenient 360° (all angle) spray system
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX38302	6130008000	£6.11	£5.40



- Greaseless lubricant preventing electrical and electronic malfunction caused by water penetration, humidity, condensation or corrosion
- Low surface tension, high capillary action formula provides great penetrating and wetting power
- Prevents corrosion by displacing moisture
- Restores resistance value by reducing current leakage
- Provides precision lubrication by its thin, high dielectric strength, lubricating film
- Helps restore water-damaged electrical equipment
- Frees rusted or seized parts by penetrating under dirt and scale into the finest pores and cracks
- Can be used on all metal and alloys
- Will not harm modern plastics, painted surfaces, coatings and rubbers
- Convenient 360° (all angle) spray system
- 400ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX40387	6130009000	£5.40	£4.77

Clear Penetrating Oil



- High-performance oil
- Works deeply to release seized and rusted components
- Leaves a clear film of lubricant to protect against further corrosion
- 400ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX52487	R-212	£3.00	£2.69

Graphite Penetrating Spray



- Enhanced penetrating lubricant
- Penetrates and helps remove rust
- Incorporates Graphite for long lasting lubrication under arduous conditions
- Maximum working temperature 150°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX42652	R-209X400ML	£3.46	£3.10

MECRO Penetrating Oil



MECRO

- Designed to rapidly penetrate rusted, seized and corroded bolts, nuts, studs, pins, hinges, locks, linkages and tools
- Highly recommended for use in engineering, construction, transport and marine applications
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45561	PENETRANT-OIL-600	£4.48	£4.02

MECRO Maintenance Oil



MECRO

- Heavy duty multi purpose oil
- Repels and displace moisture from moving parts and electrical apparatus
- Protects against rust and corrosion
- Lubricates and releases metal components
- Eliminates squeaks caused through friction
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45560	MAINTENANCE-600	£4.63	£4.16

Spray Grease

MECRO HD Red Grease



MECRO

- Specially formulated liquid that cures to grease on contact with air
- Operates within a wide temperature range from -25°C to +250°C
- Good rust and corrosion protection on metal
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45558	H/D-RED-GREASE-600	£6.44	£5.78

Silicone Grease AMS4



- Silicone grease in easy to apply aerosol form
- Provides a smooth non-melting coating that insulates, lubricates, seals, preserves and waterproofs
- Insulates high voltage parts against leaking or arcing
- Waterproofs electronics in damp or humid conditions
- Seals against moisture ingress and prevents ice build-up
- Preserves rubber against hardening or cracking
- Assists assembly of close tolerance components
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX38300	6130008500	£9.42	£8.32

Sapphire Spray Grease



- Multi-purpose EP grease, PTFE fortified aerosol
- Outstanding EP performance (355kg weld load)
- Sapphire Premier in an aerosol can
- Suitable for use as an electrical contact lubricant
- Excellent corrosion protection
- Ideal for linear bearings
- Temperature range -50°C to +200°C
- 400ml aerosol

Price Each

Order Code	Product Code	1+	4+
WX23069	34305	£11.70	£11.36

Blue Works White Lithium



- Long-lasting, extreme pressure and wear protection
- High viscosity lubricant
- Quick drying, ideal for metal-to-metal application reducing friction
- Long lasting water and heat resistant formula
- Ideal for load bearing application
- Water and heat resistant
- Sprays on evenly as a liquid, sets dry for a thick, protective coating
- Effective performance at temperatures from -18°C to +145°C
- NSF H2 Registered No 143810
- 400ml aerosol

Price Each

Order Code	Product Code	1+	12+
WX52495	44422	£5.82	£5.52

Chain Lubricants

Chain and Drive Spray



- High performance EP chain and conveyor lubricant in an aerosol
- Ideal for humid conditions
- Water repellent to increase lubrication
- Excellent corrosion protection
- Applied film has good adhesion, reducing dripping or throw off
- Outstanding EP performance (200kg weld load)
- Temperature range -30°C to +150°C
- 300ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23057	22001	£12.39	£12.03

Chainspray



- Chain and Drive Lubricant
- A high solids, heat dissipating lubricant
- Offers maximum adhesion to chain links
- Resists 'water wash off' and dust absorption
- Resists 'throw off' and can be applied to running chains
- High temperature resistance up to +300°C
- Meets military specifications - Def. Stan D/DQA/TS/CS/217/1
- Pencil jet spray pattern to facilitate accurate application
- 400ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX40388	6150001100	£8.79	£7.77

Molykote MKL-N



- Mineral chain oil with solid lubricant
- Heavy duty with excellent protection against wear
- Good penetration and adhesion
- Corrosion protection
- Temperature range -25°C to +160°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX34048	MKL-N	£8.34	£7.65

Chainguard Hi-Load Spray



- High performance EP chain and conveyor lubricant
- Thin, water resistant film with molybdenum disulphide (MoS₂) for good load carrying capabilities
- Outstanding EP performance (250kg weld load)
- Applied film has good adhesion, reducing dripping or throw off
- Temperature range -30°C to +180°C
- 300ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23058	22141	£14.31	£13.90

FLT Chainlube



- Specially formulated for use on fork lift trucks
- Applications include chains, drives and tail-lifts
- Excellent penetration and tenacity for long lasting lubrication
- Resists water wash-off
- Protects against corrosion
- 500ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX40389	6170030010	£4.04	£3.57

Clear Polymer Chain Spray



- Clear polymer based lubricant Fortified with PTFE for chains, sprockets, pins and bushes
- High anti-filing performance
- Resists and prevents corrosion
- Clean to use
- Penetrates deeply
- Withstands pressure cleaning
- Temperature range -50°C to +150°C continuous, 300°C intermittent
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX42653	R-228X400ML	£3.52	£3.16

MECRO H/D Synthetic



- Specially formulated synthetic oil for rapid penetration between links, rollers and pins
- Excellent long term protection against wear and abrasive dust
- Regular application ensures that lubrication is maintained between all working surfaces
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45559	H/D-SYNTH-OIL-600	£5.52	£4.95

MECRO H/D Chain Oil



- Penetrates between link, rollers and pins
- Long term heavy duty protection against wear and abrasive dust
- Regular application ensures that lubrication is maintained between all working surfaces
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45557	H/D-CHAINOIL-600	£5.63	£5.05

Gear and Wire Rope Lubricants

Rocol Tufgear Spray



- Thin tenacious film
- High viscosity, non-melting lubricant
- Excellent load carrying capacity
- Does not attract dust and dirt
- Withstands wet conditions
- Temperature range of -10°C to +100°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23055	18105	£19.24	£18.68

Rocol Wire Rope Spray



- Aerosol applied Wire Rope lubricant containing molybdenum disulphide (MoS₂) and other anti-wear additives
- Withstands extreme wet / corrosive conditions
- Excellent internal & external wear & corrosion protection
- High performance - ensures extended relubrication intervals
- Thin film resists dust and dirt build-up
- Wire ropes are cleaner to handle and inspect
- Temperature range -30°C to +100°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23056	20015	£16.91	£16.42

Gear and Wire Rope




- A fast drying, high solids, high penetrating lubricant
- Deep penetration for internal protection of wire ropes
- Forms a dry non-peeling film that overcomes the limitations of grease lubrication and pressure cushions
- Pencil jet spray pattern to facilitate accurate application
- Suitable for use on gears in motion
- Suitable for gears at all speeds
- Temperature range of -25°C to +100°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX38301	6150007000	£9.19	£8.12

Wire and Chain Spray



- Heavy duty molybdenum disulphide (MoS₂) reinforced lubricant
- Penetrates deeply into drive chains and wire ropes to give long lasting lubrication
- Extreme pressure additives for heavy loads
- Resistant to flinging off
- Temperature range -10°C to +180°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX42654	R-220X400ML	£3.63	£3.26

MECRO Machine Oil FG



- A colourless, odourless formulation that contains anti-throw additives
- Quickly penetrates cable cores
- Ideal for use on conveyors, cables, chains, cams, castors and gears etc
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45555	F/G-MACHINEOIL-600	£5.15	£4.62

Mould Release

Rocol PR Spray



- Long lasting silicone mould release
- Wet film silicone release agent
- Ultrafine even film gives controlled application with complete coverage
- Gives excellent gloss finish
- Highly economical, one pass coating
- Heat resistant wet film up to +200°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23151	72015	£11.87	£11.52

Rocol Mould Release



- Long lasting PTFE mould release
- Dry film does not carry dirt and cause staining
- Particularly suited for high speed production
- Resists oxidation and action of water, steam and all common chemicals
- Silicone free
- Operational up to +270°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23152	72021	£15.91	£15.45

Silicone Release Agent



- Heavy duty, high silicone concentration mould release agent
- Formulated for stubborn and hard to release plastic and rubber moulding
- Improves surface finish, will not build up in the mould
- Operational up to +200°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX38305	6110002500	£9.72	£8.58

Rocol RS-7



- Long lasting spray for use where neither silicone nor PTFE derivatives are acceptable
- Highly effective even gloss film
- Excellent performance when used with polypropylene, expanded polystyrene, nylon A100 and nitrile rubbers
- Can be over-painted or printed
- Heat resistant wet film - up to +150°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23153	72035	£16.60	£16.12

Mould Cleaner



- Cleaner for mould tools and dies
- Quickly and easily removes oil, grease, old protective films, silicone and non-silicone based release agents
- Evaporates to leave a clean, dry surface with no residues
- Special formulation permits use on hot production tooling without excessive solvent loss by evaporation
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	6+
WX38306	6120008000	£6.64	£5.87

Anti-Seize Products

NEVER-SEEZ®



- NEVER-SEEZ compound is a superior product for high temperature anti-seize and extreme pressure lubrication
- Fine metallic and graphite flakes in a special hydrocarbon carrier to protect against seizure, galling, rust, and fretting
- Resistant to wash-off by salt or fresh water
- Keeps parts working longer with less wear
- Enables faster dismantling when repairs are needed - reduces down-time
- Prevents heat seizure, corrosion, galvanic pitting and electrolysis

Product	Benefits
Standard	Copper based anti-seize Protection to approximately 1000°C
Nickel	Nickel based anti-seize Excellent performance in acid or alkaline environments Protection to approximately 1300°C
Nuclear	Nickel based anti-seize Specially tested and certified for purity Excellent performance in acid or alkaline environments Protection to approximately 1300°C

Price Each

Order Code	Product Code	Description	1+	6+
WX42656	NS-160	Standard 1lb	£23.25	£21.33
WX42657	NSBT-8N	Nickel 8oz	£28.20	£25.85
WX42658	NS-165NI	Nickel 1lb	£35.55	£32.60
WX42659	NG-165	Nuclear 1lb	£45.00	£41.15

Anti-Seize Compound



- A copper based anti-seize paste containing a high level of metallic and lubricating solids
- Use to prevent galling and seizure of screws, bolts, studs and other static threaded fasteners
- Effective even in the most aggressive environments
- Temperature range -10°C to +1100°C

Price Each

Order Code	Product Code	Size	1+	4+
WX23039	14030	85g	£7.01	£6.82
WX23040	14033	500g	£14.07	£13.67
WX23041	14035	6Kg	£159.17	£154.86
WX23042 ‡	14038	18Kg	£406.94	£395.95

‡ Special delivery applies. Please call for details

Anti-Seize Stainless



- Specially formulated for nimonic and stainless steel
- Nickel-free paste designed specifically for nimonic, stainless and silver coated fasteners
- Provides even torque loads and prevents galling and pick up on assembly
- Protects against wet conditions and chemical attack
- Excellent anti seize properties over extended periods at high temperatures
- Contains extremely low levels of chlorine and sulphur
- Formerly known as ASC251T
- Approved to MSRR 4008, Rolls Royce Plc OMAT Item 4/62
- Temperature range -40°C to 1000°C
- 500g/m tin

Price Each

Order Code	Product Code	1+	4+
WX45571	14143	£84.97	£82.68

Loctite Copper Antiseize Stick 8065



- Clean and convenient packaging
- General purpose copper anti-seize
- High copper content, premium quality
- For use up to +980°C

Price Each

Order Code	Product Code	1+	4+
WX31665	8065X20GRM	£6.78	£6.52

Molykote 1000 Thread Paste



- Solid lubricant paste for bolted metal joints; contains no lead or nickel
- Enables non-destructive dismantling of joints even after long use at high temperatures
- High load-carrying capacity
- Good corrosion protection
- Temperature range -30°C to +650°C

Price Each

Order Code	Product Code	Size	1+	6+
WX33956	1000X400ML	400 ml Aerosol	£13.94	£12.78
WX33957	1000X100GRM	100g Tube	£5.04	£4.62
WX33959	1000X1KG	1 Kg	£26.94	£24.69

Anti-Seize Spray

Rocol Anti-Seize Spray



- Copper based anti-seize, lead free formulation
- Effective even in the most aggressive environments
- Use on all threaded and static fasteners
- Lubricates, protects and eases dismantling
- Excellent water resistance
- Temperature range -10°C to +1100°C
- 400ml Aerosol

Price Each

Order Code	Product Code	1+	4+
WX23027	14015	£18.64	£18.10

Mecro Copper Anti-Seize



- Excellent protection for metal parts against heat, seizure, rust, corrosion, water and acid
- Forms a protective coating that will not wash or burn off
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45554	A/S-COPPER-600	£5.88	£5.28

Mecro Aluminium Anti-Seize



- Protection for metal parts against heat, seizure, rust, corrosion, water and acid
- Lubricates moving metal parts at high temperatures
- Specialised formula forms a protective coating that will not wash or burn off
- 600ml aerosol

Price Each

Order Code	Product Code	1+	6+
WX45553	A/S-ALUMINIUM-600	£5.52	£4.95

Petrol and Diesel Engine Oils

Havoline Energy 5W-30



- Havoline energy 5W/30
- A unique, race-proven, fuel-efficient engine oil which gives:
- A saving on fuel consumption
- Greater engine power by means of high performance additives
- Reduced exhaust emissions, thus helping to protect the environment
- Complete engine protection even in the most demanding conditions
- Sustained, long-life performance levels
- API SL; ACEA A1/B1-04; ISLAC GF-3; WSS M2C913B

Price Each

Order Code	Product Code	1+	4+
WX23220	HAVOLINENERGY5LTR	£24.04	£22.73
WX33977	HAVOLINENERGY20LT	£81.54	£77.09
WX33978 ‡	HAVOLINENERGY208LTR	£780.00	£737.45

‡ Special delivery applies. Please call for details

Ursa Super LA 15W-40



- Mixed Fleet engine oil
- Protects against sludge and deposits - greater efficiency, reduced emissions and fuel consumption
- Can minimise friction and wear at start up - reduced maintenance costs/longer engine life
- Resists viscosity and thermal breakdown - even in severe service and with extended drain periods
- Provides protection against bearing corrosion - increased durability even with extended oil drains
- ACEA A2-96, B2-98, E2-96
- API CG-4/SJ, MAN 271, MB Approval 228.1/229.1, MTU Type 1, Volvo VDS, MACK EO-L, Allison C4

Price Each

Order Code	Product Code	1+	4+
WX42696	URSASUPLA15X20LTR	£71.15	£67.27
WX42697 ‡	URSASUPLA15X208LTR	£740.00	£699.64

‡ Special delivery applies. Please call for details

Antifreeze

Havoline Extended Life Antifreeze Coolant



- Ethylene glycol based advanced formulation which contains carboxylic acid technology
- Delivers exceptional maintenance free performance: 650,000km; up to 5 years in trucks and buses; 350,000 km/2000hrs in passenger cars; 32,000 hrs in stationary engines
- ASTM D3306/D4656/D4985, BS 6580, SAE J1034, MB 325.3, Deutz 0199-99-1115 (2) & 0199-99-2091 (4), MTU MTL 5048

Price Each

Order Code	Product Code	1+	4+
WX42698	HAVOLINE XLC+B2 (OF02) 20Ltr	£92.31	£87.27
WX45592 ‡	HAVOLINE XLC+B2 (OF02) 210Ltr	£1058.08	£1000.36

‡ Special delivery applies. Please call for details

Hydraulic Oils

Texaco Rando HD Oils



- Rando HD hydraulic oils are a series of high quality, solvent-refined lubricants
- Blended with rust and oxidation inhibitors and anti-wear additives
- Recommended for use in all high-performance, heavy duty hydraulic systems, including high speed/pressure vane, gear and axial piston pumps
- Rando HD oils comply with the performance requirements of the following specifications:
- Denison HF-0 and HF-2; Sperry Vickers M-2950-S, 1-286-S; Cincinnati Milacron P68 (HM-32), P69 (HM-68), P70 (HM-46); DIN 51524 part 2 HLP; AFNOR NF E 48 603; General Motors LH-04-1, LH-06-1, LH-15-1; US Steel 136, 127.
- Available in 1,000 Ltr IBC and bulk deliveries - please call for details

Price Each

Order Code	Product Code	1+	4+
WX38323	RANDOHD10X20LTR	£61.54	£58.18
WX38324 ‡	RANDOHD10X208LTR	£576.00	£544.58
WX33985	RANDOHD32X20LTR	£61.54	£58.18
WX33986 ‡	RANDOHD32X208LTR	£576.00	£544.58
WX33987	RANDOHD46X20LTR	£61.54	£58.18
WX33988 ‡	RANDOHD46X208LTR	£576.00	£544.58
WX33989	RANDOHD68X20LTR	£59.62	£56.36
WX33990 ‡	RANDOHD68X208LTR	£576.00	£544.58
WX40391 ‡	RANDOHD100X208LTR	£576.00	£544.58
WX42699 ‡	RANDOHD150X208LTR	£580.00	£548.36

‡ Special delivery applies. Please call for details

Texaco Rando HDZ Oils

- RANDO HDZ oils are an extension of the RANDO Oil HD series incorporating a shear-stable viscosity index improver additive
- These grades exhibit all the qualities of the HD series and additionally have "multi-grade" viscosity properties
- Provide real and very significant "crossgrading" benefits and stay in grade, even when subjected to the shearing condition of high speed, high pressure hydraulic systems in severe service
- Contains rust and oxidation inhibitors and a specially selected anti-foamant that permits the rapid release of entrained air and water
- Available in 1,000 Ltr IBC and bulk deliveries - please call for details

Price Each

Order Code	Product Code	1+	4+
WX38326	RANDOHDZ15X20LTR	£71.15	£67.27
WX42700 ‡	RANDOHDZ15X208LTR	£672.00	£635.35
WX38327	RANDOHDZ32X20LTR	£73.46	£69.45
WX38328 ‡	RANDOHDZ32X208LTR	£728.00	£688.29
WX38329	RANDOHDZ46X20LTR	£73.46	£69.45
WX38330 ‡	RANDOHDZ46X208LTR	£648.00	£612.65
WX38331	RANDOHDZ68X20LTR	£73.46	£69.45
WX40392 ‡	RANDOHDZ68X208LTR	£648.00	£612.65

‡ Special delivery applies. Please call for details

Sapphire Hi-Power



- A range of mineral oil based thermally stable lubricating oils
- The unique formulation of Sapphire Hi-Power ensures the range is suitable for use in both hydraulic systems and as a compressor oil
- Incorporation of the L-CO System ensures compatibility with most compressors and a low level of oil carry over into the air stream
- Designed for use in compressor, hydraulic and air-line systems
- Premium quality ensures no sludge, no deposits & no varnish in hydraulics
- Increased resistance to oxidation at high temperatures
- Low foaming
- Temperature range -20°C to +120°C
- Excellent filterability

Hi Power 22

Price Each

Order Code	Product Code	Size	1+	4+
WX33998	52525	20 Ltr	£124.93	£121.55
WX33999 ‡	52529	200 Ltr	£955.13	£929.31

Hi-Power 32

Price Each

Order Code	Product Code	Size	1+	4+
WX34000	52545	20 Ltr	£98.46	£95.80
WX34001 ‡	52549	200 Ltr	£645.56	£628.11

Hi-Power 46

Price Each

Order Code	Product Code	Size	1+	4+
WX34002	52555	20 Ltr	£98.46	£95.80
WX34003 ‡	52559	200 Ltr	£645.56	£628.11

Hi-Power 68

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34004	52565	20 Ltr	£98.46	£95.80
WX34005 ‡	52569	200 Ltr	£645.56	£628.11

Hi-Power 100

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34006	52575	20 Ltr	£98.46	£95.80
WX34007 ‡	52579	200 Ltr	£645.56	£628.11

‡ Special delivery applies. Please call for details

Texaco Hydra



- Premium quality biodegradable HE hydraulic fluid
- Designed to offer improved and reliable environmental protection delivering outstanding Water Hazard Class Performance
- Zinc Free
- Excellent anti-rust, anti-oxidation and anti-wear properties
- Meets CEC-L-33-A-93
- Temperature range -30°C to 95°C

Order Code	Product Code	Size	Price Each	
			1+	4+
WX42701	HYDRA46-BIOX20LTR	20 Ltr	£146.54	£138.55
WX42702 ‡	HYDRA46BIODEX208LTR	200 Ltr	£1456.00	£1376.58

‡ Special delivery applies. Please call for details

Circulating/Turbine Oils

Texaco Regal EP Oils



- Premium quality rust and oxidation-inhibited circulating/turbine oils
- High performance additive package providing good stability, anti-corrosion and anti-wear properties
- Very effective anti-foamant additive

Regal Premium EP

- Regal Premium EP grades are ultra high performance combined cycle gas turbine oils
- Used in a wide range of equipment associated with turbine systems, including compressors, bearings, gear sets, pumps, motors, hydraulic systems

Order Code	Product Code	Size	Price Each	
			1+	4+
WX40393 ‡	REGALEP32X208LTR	200 Ltr	£684.00	£646.69
WX40394 ‡	REGALEP46X208LTR	200 Ltr	£696.00	£658.04
WX40395 ‡	REGALEP68X208LTR	200 Ltr	£696.00	£658.04

Regal EP

- Heavy duty circulating oils formulated for use in large compressors, hydraulic and circulating systems in industrial applications due to excellent demulsibility and resistance to rust and oxidation

Order Code	Product Code	Size	Price Each	
			1+	4+
WX42703 ‡	REGALEP100X208LTR	200 Ltr	£696.00	£658.04
WX42704 ‡	REGALEP150X208LTR	200 Ltr	£696.00	£658.04
WX40396 ‡	REGALEP220X208LTR	200 Ltr	£696.00	£658.04
WX40397 ‡	REGALEP320X208LTR	200 Ltr	£684.00	£646.69

‡ Special delivery applies. Please call for details

Compressor Oils

Texaco Compressor Oil EP VDL



- Premium air compressor oil with ash-free additive package
- High anti-foam and water separation properties
- For use in mobile and stationary compressors with operating temperature as high as +220°C
- High corrosion resistance, very low carbon forming tendencies
- Developed to meet the increasing demand for compressor oils which meet the DIN 51506 VD-L requirements with additional extreme pressure characteristics

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34009	COMP-EPVDL46X20LTR	20 Ltr	£79.23	£74.91
WX34010	COMP-EPVDL68X20LTR	20 Ltr	£79.23	£74.91
WX42705 ‡	COMP-EPVDL100X20LTR	200 Ltr	£76.92	£72.73

Texaco Capella WF



- Outstanding super-low freon floc temperature and pour point performance to refrigeration and air conditioning units
- Does not 'wax-out' under the low temperature conditions typically encountered in refrigerating systems
- Specially refined to be resistant to reaction with commonly used refrigerants such as ammonia and the fluorinated hydrocarbons R-12 and R-22
- Refined and treated during the course of manufacture to prevent foaming
- Exceeds DIN 51.503; BS 2626/1977

Order Code	Product Code	Size	Price Each	
			1+	4+
WX45585	CAPELLA-WF46X20LTR	20 Ltr	£90.38	£85.45
WX45584 ‡	CAPELLA-WF46X208LTR	200 Ltr	£872.00	£824.44
WX40399	CAPELLA-WF68X20LTR	20 Ltr	£90.38	£85.45
WX45586 ‡	CAPELLA-WF68X208LTR	200 Ltr	£872.00	£824.44

‡ Special delivery applies. Please call for details

Texaco Cetus PAO



- High performance protection
- Long service stability
- Drain intervals to 8000 hours
- PAO synthetic technology
- Specification to DIN 51506VDL
- Approved by Atlas Copco, Tanabe, ABB

Order Code	Product Code	Size	Price Each	
			1+	4+
WX45588	CETUS-PAO46X20LTR	20 Ltr	£232.69	£220.00
WX45587 ‡	CETUS-PAO46X208LTR	200 Ltr	£2596.00	£2454.40
WX45590	CETUS-PAO68X20LTR	20 Ltr	£232.69	£220.00
WX45589 ‡	CETUS-PAO68X208LTR	200 Ltr	£2532.00	£2393.89

‡ Special delivery applies. Please call for details

Gear Oils

Texaco Meropa



- Meropa is a range of mineral industrial gear oils
- Formulated with extreme pressure additives
- Enhanced thermal stability and substantially minimises sludge formation
- Long service life, retains good demulsibility and low foaming characteristics
- Providing a high level of performance on heavily loaded applications and outstanding protection against micro-pitting
- Meets the requirements of DIN 51517 Part 3 (CLP); US Steel 224 and David Brown ET 33/80 specification

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34012	MEROPA68X20LTR	20 Ltr	£70.00	£66.18
WX34013 ‡	MEROPA68X208LTR	200 Ltr	£684.00	£646.69
WX34014	MEROPA100X20LTR	20 Ltr	£72.31	£68.36
WX34015 ‡	MEROPA100X208LTR	200 Ltr	£684.00	£646.69
WX34016	MEROPA150X20LTR	20 Ltr	£72.31	£68.36
WX34017 ‡	MEROPA150X208LTR	200 Ltr	£684.00	£646.69
WX34018	MEROPA220X20LTR	20 Ltr	£72.31	£68.36
WX34019 ‡	MEROPA220X208LTR	200 Ltr	£684.00	£646.69
WX34020	MEROPA320X20LTR	20 Ltr	£72.31	£68.36
WX34021 ‡	MEROPA320X208LTR	200 Ltr	£684.00	£646.69
WX34022	MEROPA460X20LTR	20 Ltr	£72.31	£68.36
WX34023 ‡	MEROPA460X208LTR	200 Ltr	£684.00	£646.69
WX34024	MEROPA680X20LTR	20 Ltr	£72.31	£68.36
WX34025 ‡	MEROPA680X208LTR	200 Ltr	£684.00	£646.69

‡ Special delivery applies. Please call for details

Sapphire Hi-Torque



- A range of thermally stable semi-synthetic gearbox lubricants.
- All grades incorporate the Rocol SUPs system to provide added protection to the gears on start up.
- Highly advanced, the Hi-Torque range has been designed to operate under the high loads found in today's high performance gearboxes.
- Superior load carrying capacity.
- High thermal stability.
- Excellent corrosion protection.
- Very low foaming in operation.
- Temperature range -20°C to +120°C

Hi Torque 100

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34026	21006	5 Ltr	£117.50	£114.32
WX34027	21005	20 Ltr	£380.13	£369.85

Hi Torque 220

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34028	21016	5 Ltr	£117.50	£114.32
WX34029	21015	20 Ltr	£380.13	£369.85

Hi Torque 320

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34030	21026	5 Ltr	£117.50	£114.32
WX34031	21025	20 Ltr	£380.13	£369.85

Hi Torque 460

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34032	21036	5 Ltr	£117.50	£114.32
WX34033	21035	20 Ltr	£380.13	£369.85

Hi Torque 680

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34034	21046	5 Ltr	£117.50	£114.32
WX34035	21045	20 Ltr	£380.13	£369.85

Texaco Synlube WS



- Ultra high performance fully synthetic gear lubricants designed to provide high level EP wear protection to gears & bearings
- Synlube WS has been proven to give energy savings of between 5 to 14% against conventional mineral and PAO synthetic gear oils (Particularly in high sliding applications such as worm, helical and off set gears)
- Extreme loading capability
- Extended high temperature operating capability
- Extreme temperature thermal stability increases oil life, saving time & expense
- Low temperature fluidity improves cold-start performance and energy efficiency
- Reduces operating temperature
- Superior high temperature viscosity characteristics
- Full synthetic lubricant offering excellent long term gear protection and service life. (Up to 3 times longer than a mineral oil)
- Can be used in 'lubricate for life' applications
- Recommended for use with helical, bevel helical, planetary and worm gears, chains and conveyers, sliding and roller bearings in high load/EP applications
- DIN 51517/3
- Synlube WS is based on water soluble polyalkylene glycols and should not be mixed with mineral, PAO or non water soluble PAG lubricants

Order Code	Product Code	1+	4+
WX42706 ‡	SYNLUBEWS220X20LTR	£335.38	£317.09
WX42707	SYNLUBEWS320X20LTR	£335.38	£317.09
WX42708	SYNLUBEWS460X20LTR	£335.38	£317.09
WX42709 ‡	SYNLUBEWS460X208LTR	£3400.00	£3214.55
WX42710 ‡	SYNLUBEWS680X208LTR	£3437.69	£3250.18

Texaco Pinnacle EP



- Pinnacle EP is a synthetic poly-alpha-olefin based gear oil
- As it is a synthetic PAO gear oil it should not be mixed with either polyglycol or mineral based oils
- Resist foaming and release air rapidly
- Non-corrosive towards copper and protects against system rusting
- Naturally high VI and low pour points provide improved cold weather performance and lower viscous drag losses at operating temperatures
- This lubricant is also suitable as a circulating oil

Order Code	Product Code	1+	4+
WX40400 ‡	PINACLEEP150X208LTR	£2036.00	£1924.95
WX42711	PINACLEEP220X20LTR	£201.92	£190.91
WX40401 ‡	PINACLEEP220X208LTR	£2036.00	£1924.95
WX38334	PINACLEEP320X20LTR	£204.23	£193.09
WX40402 ‡	PINACLEEP320X208LTR	£2036.00	£1924.95
WX42712 ‡	PINACLEEP460X208LTR	£2056.00	£1943.85

‡ Special delivery applies. Please call for details

Need advice? FREE technical support at every Brammer branch

Open Gear Lubricants

Texclad



- NLGI 2 calcium grease containing a very thick base oil and a mixture of molybdenum disulphide (MoS₂) and graphite
- Extremely durable bitumen-free formulation
- Its tenacious attribute makes it ideal for use on; exposed gears, steel mill slipper drives, fork lift mast slides, fifth wheels, ball mill gears, marine wire ropes and large enclosed spur gears where oil leakage is a problem
- Temperature range -10°C to +60°C
- Highly pumpable down to 0°C

Order Code	Product Code	1+	4+
WX34043	TEXCLAD2X18KG	£132.58	£125.35

Texclad AL HVO



- Sprayable formulation
- Resistance to wear, water and oxidation
- High temperature protection
- Specification to DIN 51502 OGPFS OS-20

Order Code	Product Code	1+	4+
WX45609 ‡	TEXCLADAL-HVOX180KG	£2042.31	£1930.91

‡ Special delivery applies. Please call for details

Texclad AL EP 1&2





- High performance aluminium complex grease
- Resistance to wear, water and oxidation
- High temperature protection
- Temperature range -25°C to +150°C, with re-lubrication up to +200°C
- Specification to DIN 51502 KP2 P-20

Price Each

Order Code	Product Code	1+	4+
WX45607 ‡	TEXCLADAL-EP1X180KG	£1592.31	£1505.45
WX45608 ‡	TEXCLADAL-EP2X180KG	£1609.62	£1521.82

‡ Special delivery applies. Please call for details

Texclad AL EP 0



- High performance aluminium complex grease with very fine graphite particles
- Resistance to wear, water and oxidation
- High temperature protection
- Temperature range -20°C to +200°C, with re-lubrication up to +250°C
- Specification to DIN 51502 OGPFS OS-20

Price Each

Order Code	Product Code	1+	4+
WX45606 ‡	TEXCLADAL-EPOX180KG	£1626.92	£1538.18

‡ Special delivery applies. Please call for details

Wind Turbine Lubricants

Texaco Rando WM



- High performance multigrade hydraulic oil
- High VI provides a very wide operating temperature window
- Low pour point for optimum pumpability in low temperature start-ups
- Superior anti-wear performance and corrosion resistance
- High thermal stability prevents oil degradation and deposit formation
- Excellent filterability, shear stable
- Specification to ISO 6743/V HV, DIN 5152 HVLP
- Approved by Vestas

Price Each

Order Code	Product Code	1+	4+
WX45603	RANDO-WM32X20LTR	£138.46	£130.91
WX45602 ‡	RANDO-WM32X208LTR	£1360.00	£1285.82

‡ Special delivery applies. Please call for details

Texaco Meropa WM



- High performance industrial gear lubricant
- High level micro-pitting performance
- Advanced Extreme Pressure additives
- Rapid water separation and air release
- Thermal protection
- Corrosion resistant
- Specification to DIN 51517/3
- Approved by Flender, David Brown, Valmet

Price Each

Order Code	Product Code	1+	4+
WX45594 ‡	MEROPA-WM320X208LTR	£920.00	£869.82

‡ Special delivery applies. Please call for details

Texaco Pinnacle WM



- Ultra high performance synthetic gear lubricant
- Designed for wind turbine gear systems that are subject to adverse high load, shock load and extremely hostile environments
- Excellent micro-pitting control, improves wind turbine reliability
- Improved component protection
- Wide operating temperature range
- Rapid water separation
- Specification to DIN 51517/3
- Approved by Moventas, David Brown, Bosch Rexroth, Valmet

Price Each

Order Code	Product Code	1+	4+
WX45601	PINNACLE-WM320X20LTR	£319.23	£301.82

Chain and Drive Oils

Chain and Drive Fluid



- Multi-purpose chain lubricant for drive and conveyor chains
- Good load carrying properties
- Long term lubrication
- Penetrates links and pin
- Temperature range -15°C to +120°C

Price Each

Order Code	Product Code	Size	1+	4+
WX34044	22306	5 Ltr	£73.35	£71.36
WX34045	22309	20 Ltr	£288.86	£281.05

Chain Guard 280



- High temperature chain lubricant with excellent load carrying performance
- Moly containing for increased lubrication
- Can be used on bearings
- Ideal for bakery and paint stoving ovens
- Temperature range 0°C to +280°C

Price Each

Order Code	Product Code	Size	1+	4+
WX34046	22235	5 Ltr	£195.90	£190.61
WX34047	22236	20 Ltr	£739.07	£719.09

Wire Rope Lubricants

Wireshield



- A high performance wire rope lubricant
- Excellent lubrication properties to reduce wear on wires and strands
- Maximises service life
- Translucent film allows easier and more effective rope inspection
- Does not drip or fling off due to the pseudo-plastic rheology
- Thin, non-tacky film prevents build-up of dust and dirt
- Highly resistant to water wash-off
- Clean and pleasant to use
- Outstanding corrosion protection
- Highly resistant to water wash-off
- Temperature range -30°C to +100°C

Price Each

Order Code	Product Code	Size	1+	4+
WX45577 ‡	20054	18Kg	£232.49	£226.20
WX45578 ‡	20058	160Kg	£1859.93	£1809.66

‡ Special delivery applies. Please call for details

Wire Rope Dressing



- High performance, semi-fluid wire rope lubricant containing a unique combination of lubricating solids
- Totally water repellent, cannot emulsify in water and, due to its non-tacky nature, will prevent build up of dust and contaminants on the rope
- Used successfully on hoists, drag lines, cranes and ships, particularly in areas where salt water, dust, sand, effluent or other hostile conditions prevail
- Excellent internal & external wear and corrosion protection
- Thin film keeps ropes clean from dust and dirt and are cleaner to handle
- Does not drip or fling off
- Also suitable as a gearbox grease for slow moving, highly loaded boxes
- NLGI No. 00
- Temperature range -30°C to +100°C

Price Each

Order Code	Product Code	Size	1+	4+
WX45576	20026	4Kg	£76.03	£73.97
WX45575	20024	18Kg	£319.86	£311.22

Bearing Greases

Sapphire 1



- Triple life bearing grease
- Extended lubrication intervals
- Revolutionary multi-complex grease
- Excellent load carrying capacity
- Good corrosion resistance
- Sapphire 1 is NLGI 1, and ideal for remote lubrication or long pipe run applications
- Temp range -30°C to +150°C

Price Each

Order Code	Product Code	Size	1+	4+
WX23018	12601	400g Cartridge	£6.72	£6.54
WX23019	12606	5 Kg	£69.92	£68.03
WX23021	12614	18 Kg	£217.96	£212.07
WX23022	12608	50 Kg	£564.79	£549.53
WX23023 ‡	12609	185 Kg	£1393.25	£1355.59

‡ Special delivery applies. Please call for details

Texaco Multifak EP 1



- Lithium based mineral grease containing extreme pressure additives
- NLGI No 1 grease suitable for ball and roller bearings
- Protects against rust and resists water washout
- Non-corrosive to non-ferrous bearing metals as well as steel
- Temperature range -30°C and +120°C

Price Each

Order Code	Product Code	1+	4+
WX23247	MULTIFAKEP1X18KG	£99.35	£93.93
WX45598 ‡	MULTIFAKEP1X180KG	£958.85	£906.55

‡ Special delivery applies. Please call for details

Sapphire 2



- Triple life bearing grease
- Extended lubrication intervals
- Revolutionary multi-complex grease
- Excellent load carrying capacity
- Good corrosion resistance
- NLGI 2
- Temperature range -30°C to +150°C

Price Each

Order Code	Product Code	Size	1+	4+
WX23002	12171	400g Cartridge	£6.31	£6.13
WX23003	12176	5kg	£69.92	£68.03
WX23005	12175	18kg	£217.96	£212.07
WX23006	12178	50kg	£555.83	£540.81
WX23007 ‡	12179	185kg	£1304.17	£1268.92

‡ Special delivery applies. Please call for details

Texaco Multifak EP 2



- Extreme pressure multi-purpose industrial lithium soap product
- Protects non-ferrous bearing metal as well as steel
- Temperature range -30°C to +120°C. Short exposure to +140°C

Price Each

Order Code	Product Code	1+	4+
WX23244	MULTIFAKEP2X400GRM	£2.90	£2.74
WX34081	MULTIFAKEP2X18KG	£101.08	£95.56
WX23245 ‡	MULTIFAKEP2X50KG	£281.73	£266.36
WX23243 ‡	MULTIFAKEP2X180KG	£810.00	£765.82

‡ Special delivery applies. Please call for details

Molykote Multilub



- High performance grease for metal/metal combinations involving slow to fast movements and medium to high loads
- Lithium based beige grease with EP additive
- Good load carrying capacity
- Suitable for long-term lubrication
- Good water washout and corrosion resistance properties
- NLGI class 2
- Temperature range -25°C to +120°C

Price Each

Order Code	Product Code	Size	1+	6+
WX34064	MULTILUBX100GRM	100g Tube	£3.30	£3.03
WX34065	MULTILUBX400GRM	400g Cartridge	£3.70	£3.40
WX34066	MULTILUBX1KG	1 Kg	£10.58	£9.70
WX45567 ‡	MULTILUBX5KG	5 Kg	£38.93	£35.68

‡ Special delivery applies. Please call for details

Ambergrease EXL



- Extended life bearing grease
- Red Lithium-Calcium Multi Complex
- NLGI 2 grease with excellent hi-load characteristics
- Suitable for use in all anti-friction plain bearings
- Operational temperature range: -30°C to +150°C
- 400grm cartridge

Price Each

Order Code	Product Code	1+	6+
WX52486	6150001010	£5.92	£5.23

For condition monitoring, see our Test & Measurement section



Sapphire Advance 2



- Ultimate multi-purpose grease
- Lithium EP grease fortified with PTFE for maximum life of ball, roller and plain bearings
- Designed for high load, cyclical, rapid start-stop applications
- Outstanding EP performance (560kg weld load)
- Excels in high speed applications
- Excellent corrosion protection
- Ideal for fan bearings and electric motors
- NLGI 2
- Temperature range -30°C to +160°C

Price Each

Order Code	Product Code	Size	1+	4+
WX45568	12441	380g Cartridge	£7.39	£7.19
WX45569	12444	4Kg	£69.92	£68.03
WX45570 ‡	12446	18Kg	£239.76	£233.28

‡ Special delivery applies. Please call for details

Sapphire Premier



- Multipurpose EP grease fortified with PTFE
- Excellent high speed capability
- Compatible with most plastics and rubbers
- Extended lubrication intervals
- Suitable for use as an electrical contact lubricant
- Typical uses - Electrical motors and fan bearings
- Ideal for linear bearings
- NLGI 2
- Temperature range -50°C to +200°C

Price Each

Order Code	Product Code	Size	1+	4+
WX23013	12471	380g Cartridge	£24.14	£23.49
WX23014	12475	4Kg	£175.90	£171.15
WX23016	12474	18Kg	£730.67	£710.92
WX23017 ‡	12479	170Kg	£2488.00	£2420.76

‡ Special delivery applies. Please call for details

Sapphire Hi-Pressure



- A high Moly content grease designed for heavy load carrying in plain bearings
- High load carrying capacity - reduces wear
- Excellent corrosion protection
- High resistance to water wash-out
- Extended lubrication intervals
- NLGI 2
- Temperature range -20°C to +150°C

Price Each

Order Code	Product Code	Size	1+	4+
WX34053	12011	400g Cartridge	£15.51	£15.09
WX34054	12013	500g Tin	£18.16	£17.64
WX34055	12016	5 Kg	£138.00	£134.27
WX34056	12024	18 Kg	£458.47	£446.08
WX34057 ‡	12018	50 Kg	£1203.49	£1170.96

‡ Special delivery applies. Please call for details

Sapphire AQUA 2



- Sapphire AQUA 2 is an aluminium soap thickened grease designed to give superior resistance to water wash-out
- Gives exceptional corrosion protection and long term lubrication for bearings operating in water or exposed to continual water washing
- Outstanding water resistance - even when submerged
- Excellent corrosion protection
- Extended lubrication intervals
- Good wear resistance
- NLGI 2
- Temperature range -20°C to +150°C

Price Each

Order Code	Product Code	Size	1+	4+
WX34058	12751	380g Cartridge	£12.44	£12.11
WX34059	12755	4 Kg	£91.47	£89.00
WX34060	12754	18 Kg	£384.90	£374.50

Texaco Starplex



- High performance multi-service green lithium grease
- Ultimate long service protection to ball and roller bearings
- High to low speeds, in wet and corrosive applications
- It is suitable for use between -35°C and 140°C
- With frequent relubrication can be used to 180°C

Price Each

Order Code	Product Code	Size	1+	4+
WX42714	STARPLEXEP2X400G		£3.32	£3.13
WX42715	STARPLEXEP2X18KG		£125.65	£118.80
WX45605 ‡	STARPLEXEP2X50KG		£337.50	£319.09
WX45604 ‡	STARPLEXEP2X180KG		£1177.37	£1113.15

‡ Special delivery applies. Please call for details

Texaco Texando F020



- Calcium complex NLGI No 2 grease
- Suitable for use in ball and roller bearing applications
- Water resistant, both against boiling water and slightly acidic or slightly alkaline solutions
- High temperature melting soap
- Temperature range -30°C to +150°C
- Short exposure to 240°C with frequent relubrication

Price Each

Order Code	Product Code	Size	1+	4+
WX23265 ‡	TEXANDOF020X180KG		£1350.00	£1276.36

‡ Special delivery applies. Please call for details

Molykote BR2+



- High performance multi-purpose black lithium based grease with EP additives
- Higher operational reliability
- Extended lubrication intervals even under high loads and difficult lubricating conditions
- NLGI class 2
- Temperature range -30°C to +130°C. Short exposure to +150°C

Price Each

Order Code	Product Code	Size	1+	6+
WX34068	BR2+X100GRM	100g Tube	£2.71	£2.49
WX34069	BR2+X400GRM	400g Cartridge	£6.03	£5.53
WX34070	BR2+X1KG	1 Kg	£11.72	£10.75
WX34071	BR2+X5KG	5 Kg	£52.14	£47.79

For Lockouts and Tagouts, see our Site Safety section



SKF Grease



SKF bearing grease for a wide range of applications

- **LGMT 2**
Lithium based NLGI 2 grease. Wide range of industrial applications. -30°C to +120°C
- **LGMT 3**
Lithium based NLGI 3 grease. Wide range of industrial applications. -30°C to +120°C
- **LGEP 2**
Lithium based NLGI 2 grease. High load extreme pressure applications. -20°C to +110°C
- **LGWA 2**
Lithium complex based NLGI 2 grease. High load, extreme pressure and temperature applications. -30°C to +140°C
- **LGHB 2**
Complex Calcium Sulphonate NLGI 2 grease. High viscosity, load and temperature applications. -20°C to +150°C
- **LGHP 2**
Polyurea NLGI 2 grease. High performance and temperature applications. -40°C to +150°C

Price Each

Order Code	Product Code	Size	1+	4+
WX45546	LGMT2/0.2	200g	£4.83	£4.59
WX45547	LGMT2/0.4	400g	£5.08	£4.82
WX45548	LGMT2/1	1Kg	£9.91	£9.41
WX45549	LGMT3/0.4	400g	£5.08	£4.82
WX45550	LGMT3/1	1Kg	£10.70	£10.16
WX45541	LGEP2/0.4	400g	£5.79	£5.50
WX45542	LGEP2/1	1Kg	£11.94	£11.34
WX45551	LGWA2/0.4	400g	£8.44	£8.01
WX45552	LGWA2/1	1Kg	£16.50	£15.67
WX45543	LGHB2/0.4	400g	£9.08	£8.62
WX45544	LGHP2/0.4	400g	£10.29	£9.77
WX45545	LGHP2/1	1Kg	£21.53	£20.45

Molykote 33 M



- Lithium soap - silicone oil composition
- Pink in colour
- Suitable for light-load applications where there is metal-to-metal or metal-to-plastic friction
- Compatible with most plastics
- Superior low-temperature characteristics
- NLGI class 2
- Temperature range -73°C to +180°C

Price Each

Order Code	Product Code	Size	1+	6+
WX34078	33MX100GRM	100g Tube	£10.82	£9.92
WX34079	33MX1KG	1 Kg	£82.17	£75.32

Molykote 44 M



- Suitable for a wide range of uses on high temperature bearings
- Typical applications include bearings in; oven fans, textile dryers, conveyors, kiln pre-heaters etc
- Superior low-temperature characteristics
- Compatible with most plastics
- Silicone oil, lithium soap
- NLGI class 2 - 3
- Temperature range -40°C to +200°C

Price Each

Order Code	Product Code	Size	1+	6+
WX34075	44MX100GRM	100g Tube	£13.30	£12.15
WX34076	44MX1KG	1 Kg	£101.50	£93.00

Texaco Multifak Premium 3



- Lithium soap grease suitable for high speed ball and roller bearings
- Particularly suited to the lubrication of electric motor bearings
- Resists water wash-out whilst providing outstanding rust and oxidation protection
- NLGI 3
- It is suitable for use between -30°C and +120°C. Short periods to +140°C

Price Each

Order Code	Product Code	1+	4+
WX34082	MULTIFAKPREMIUM3X18KG	£77.15	£72.95

Fluid Grease

Texaco Multifak 264



- Multifak 264 EP 00/000 is a high quality, heavy duty mineral based lithium grease
- Highly effective rust protection, anti-wear performance and oxidation resistance
- Can be used in centralised lubrication systems due to excellent pumpability
- It is suitable for use between -50°C and -120°C
- Recommended for railway wheel bearings, heavy duty road vehicles, roller bearings in crushers, mills, mixers
- Approved by Firma Willy Vogel, Tecalemit, Lincoln, Mercedes Benz blue Book spec 264, MAN 283 Li-P00

Price Each

Order Code	Product Code	1+	4+
WX40405	MULTIFAK264EP00X18KG	£111.12	£105.05
WX45597 ‡	MULTIFAK264EP00X50KG	£304.81	£288.18
WX45596 ‡	MULTIFAK264EP00X180KG	£1073.08	£1014.55

‡ Special delivery applies. Please call for details

Texaco Multifak EP 000



- Multifak EP 000 is a lithium based mineral grease containing extreme pressure additives
- High anti-oxidation and wear protection properties
- It is designed for use in automatic chassis lubricant equipment particularly those manufactured by Mecafluid and Interlube / Tecalmit systems fitted with paddles
- Ideal for large rolling element bearings in mining, construction and marine equipment
- Suitable for use between -30°C and 110°C. Short periods to 130°C

Price Each

Order Code	Product Code	1+	4+
WX32691	MULTIFAKEP00X18KG	£93.46	£88.36

Sapphire 000



- Triple life bearing grease NLGI 000
- Extended lubrication intervals
- Revolutionary multi-complex grease
- Excellent load carrying capacity
- Good corrosion resistance
- Outstanding EP performance (620kg weld load)
- Temperature range -30°C to +150°C
- Sapphire 000 is recommended and approved for use in centralised lubrication systems and for grease filled gearboxes

Price Each

Order Code	Product Code	Size	1+	4+
WX23008	12276	5 Kg	£69.92	£68.03
WX23010	12284	18 Kg	£217.96	£212.07

Hi-Load Greases

Sapphire Hi-Load 2



- Long life multi-purpose grease containing molybdenum disulphide (MoS₂)
- Designed for the effective lubrication and protection of all types of ball, roller and plain bearings
- Outstanding EP performance (>800kg weld load)
- Greatly extended lubrication intervals
- Typically 3 times longer than conventional soap thickened greases
- Good corrosion resistance
- Ideal for heavy loaded, slow moving applications
- NLGI No 2
- Temperature range -30°C to 150°C

Price Each

Order Code	Product Code	Size	1+	4+
WX42716	12761	400g	£13.76	£13.39
WX42717	12765	5Kg	£121.92	£118.62
WX42718	12764	18Kg	£404.97	£394.03

Texaco Molytex EP 2




- Molytex EP 2 is lithium soap grease containing both molybdenum disulphide (MoS₂) and EP additives
- Provides excellent protection against seizure under highly loaded service conditions
- Additive pack to inhibit oxidation and rust
- Well suited for use in industrial equipment, automotive, construction and mining vehicles such as bulldozers, scrapers, loaders, shovels and off-highway trucks
- Ideal for greased components that are subject to heavy loading
- Successfully used in constant velocity joints (CV-joints) in front wheel drive cars, universal joints (U-joints) and for chassis lubrication
- Temperature range -30°C to +130°C

Price Each

Order Code	Product Code	Size	1+	4+
WX23240	MOLYTEXEP2X400G		£2.55	£2.41
WX34087	MOLYTEXEP2X18KG		£99.35	£93.93
WX23241 ‡	MOLYTEXEP2X50KG		£274.04	£259.09
WX45595 ‡	MOLYTEXEP2X180KG		£951.92	£900.00

‡ Special delivery applies. Please call for details

Molykote HP870 (Formerly BG87)



- PFPE based white bearing grease fortified with PTFE
- For metal/metal and metal/plastic combinations
- Suitable for extremely high loads with slow to medium fast movements
- Highly resistant to water
- Resistant to many chemicals
- NLGI class 2
- Temperature range -35°C to +250°C (up to 280°C for short periods)

Price Each

Order Code	Product Code	Size	1+	6+
WX34089	HP870X100GRM	100g Tube	£81.48	£74.69
WX34090	HP870X1KG	1 Kg	£508.41	£466.04

Texaco Multifak T EP2



- Exceptional resistance to corrosion and oxidation
- Lithium based premium quality highly viscous semi-synthetic grease
- Maximises wear protection performance
- Highly stable, delivering maximum high-pressure load capacity
- Temperature range -20°C to +130°C
- Short periods to +150°C
- To specification DIN 51502 KP2 K-20

Price Each

Order Code	Product Code	Size	1+	4+
WX45600	MULTIFAK-T-EP2X18KG		£193.00	£183.00
WX45599 ‡	MULTIFAK-T-EP2X180KG		£1696.15	£1603.64

‡ Special delivery applies. Please call for details

Hi-Temp Grease

Sapphire Extreme



- A high performance moly grease for use in plain and roller bearings operating in arduous conditions
- Ideal for heavy loaded, high temperature applications
- Excellent resistance to vibration
- Extremely stable at high temperatures
- Excellent chemical resistance
- Excellent anti-wear properties
- NLGI 2
- Temperature range -10°C to +235°C. Short exposure to +250°C

Price Each

Order Code	Product Code	Size	1+	4+
WX34050	12211	400g Cartridge	£25.04	£24.36
WX34051	12216	5 Kg	£225.67	£219.57
WX34052	12214	18 Kg	£740.88	£720.85

Sapphire Aqua-Sil



- Silicone grease for long term lubrication at extreme temperatures
- Designed for the lubrication of slow speed bearings, slides, stenter width adjustment spindles, 'O' rings
- Good resistance to chemicals, oils, water and gases
- Does not affect most rubbers and plastics
- Suitable for use as an electrical insulating and filling compound
- WRC approved for hot and cold potable water
- Water Bylaws Scheme approved product (UKWFBS listed) for use with both hot and cold potable water
- Temperature range -40°C to +200°C. Short exposure to +220°C

Price Each

Order Code	Product Code	Size	1+	4+
WX38335	12251	85g	£13.26	£12.91
WX38336	12253	500g	£60.86	£59.22
WX38337	12256	5Kg	£426.07	£414.55

For eye protection, see our Personal Protection Equipment section



Texaco High Temp Premium 2



- High temperature stability
- Does not soften at elevated temperatures
- Highly resistant to thermal oxidation
- Poly alpha olefin based grease
- Wear, corrosion and water resistant
- NLGI class 2
- Temperature range -30°C to +180°C
- Intermittent temperature to +230°C and radiated heat to +280°C
- To specification DIN 51502 KPC H2 P-30

Price Each

Order Code	Product Code	1+	4+
WX45593	HIGHTEMPREM2X18KG	£586.73	£554.73

Water Resistant Greases

Texaco Novatex EP 2



- Calcium soap grease containing very effective extreme pressure and anti-wear additives
- Contains oxidation and corrosion inhibitors
- Particularly good under heavy water-washing conditions where extreme pressure properties must be maintained
- Very long lubricant service life
- Temperature range -30°C and +120°C

Price Each

Order Code	Product Code	1+	4+
WX34093	NOVATEXEP2X18KG	£130.50	£123.38

Gas Tap Grease

ROCOL M23660



- Effective lubrication and sealing of gas taps and taper plug cocks
- Its use enables compliance with British Standard 5494, 1978, service No.6 (30,000 operations)
- Good lubricating and sealing properties
- Excellent anti-wear and anti-seize properties
- Temperature range -20°C to +120°C for continuous use

Price Each

Order Code	Product Code	Size	1+	4+
WX38338	32020	50g	£10.29	£10.01

Molykote 1102



- Mineral oil grease for use on gas taps and cocks with metal, glass and plastic combinations
- Highly resistant to water
- No drop point therefore no melting point or leakage from lubrication points
- NLGI class 3
- Temperature range 0°C to +160°C (220°C short term)

Price Each

Order Code	Product Code	Size	1+	6+
WX34094	1102X50GRM	50g Tube	£4.16	£3.82
WX34095	1102X1KG	1 Kg	£30.45	£27.91

Coupling Grease

Texaco Coupling Grease



- Lithium soap grease with an NLGI consistency overlapping a 0 and 1 grade
- Contains a special high viscosity base oil
- Resistant to high levels of water washout and / or shock loading
- Superior resistance to oil separation makes it suitable for all types of flexible couplings as defined by AGMA Coupling Grease Specification CG1, CG2 and CG3
- Formulated to avoid the oil separation that most greases experience at high centrifugal speeds as found in couplings
- Temperature range -10°C to +120°C (short exposure up to +160°C)
- Minimum pumping temperature -7°C

Price Each

Order Code	Product Code	1+	4+
WX34096 ‡	COUPLINGGREASEX15.9K	£185.60	£175.47
WX45591 ‡	COUPLINGGREASEX54.5K	£625.71	£591.58

‡ Special delivery applies. Please call for details

'O'-ring Grease

Molykote 55



- Silicone based lubricant for 'O'-rings
- Dynamic lubrication between rubber and metal parts
- Compatible with many plastics and elastomers
- Wide service temperature range and good corrosion protection
- High oxidation resistance
- Temperature range -65°C to +175°C

Price Each

Order Code	Product Code	Size	1+	6+
WX34097	55MX100GRM	100g Tube	£10.14	£9.29
WX34098	55MX1KG	1 Kg	£72.32	£66.29

Molykote 111



- Translucent silicone oil with silica thickener
- Lubrication for control and pressure plug valves, water softener and faucet valves
- Sealant for vacuum and pressure systems
- Damping medium for dash pots in electrical and electronic equipment
- Rubber and plastic 'O'-rings, gaskets and seals
- Excellent water resistance and resistant to most chemicals
- Temperature range -40°C to +200°C

Price Each

Order Code	Product Code	Size	1+	6+
WX34099	111X100GRM	100g Tube	£8.23	£7.54
WX34100	111X400GRM	400g Cartridge	£25.39	£23.28
WX34101	111X1KG	1 Kg	£51.85	£47.53
WX45565	111X5KG	5 Kg	£245.17	£224.74

High Vacuum Grease



- Designed for sealing and lubricating vacuum and pressure systems
- Lubricates plug valves, control valves, flow meter bearings, ceramic plug cocks and fire extinguisher valves
- Lubricates water-treating equipment, synthetic rubber gaskets and seals in high-temperature applications
- Maintain vacuum and pressure systems
- Low volatility to hold deep vacuums
- Resists oxidation
- Good thermal stability
- Stiff, non-melting Translucent white silicone material
- Temperature range -40°C to +204°C
- Recommended for vacuums reaching between 1 x 10⁻⁵ and 1 x 10⁻⁶ mm Hg

Price Each

Order Code	Product Code	1+	5+
WX45566	HIGHVACX50GRM	£9.97	£9.14

Electrical Compound

DC4



- High dielectric strength translucent grease compound
- Inert silica filler in combination with selected polydimethyl silicone fluids
- Adheres readily to dry metals, ceramics, rubber, plastics and insulating resins
- Used as a seal and lubricant for cable connectors, battery terminals, rubber door seals, switches and rubber and plastic O-rings
- Assembly lubricant for various metal-on-plastic and metal-on-rubber combinations
- Non-melting, odourless, waterproofing and insulating
- Good thermal oxidation and chemical stability
- Meets MIL-S-8660C
- Service temperature -55°C to +200°C

Price Each

Order Code	Product Code	Size	1+	5+
WX34102	DC4X100GRM	100g Tube	£6.32	£5.79
WX45540 ‡	DC4X5KG	5 Kg	£245.59	£225.12

‡ Special delivery applies. Please call for details

PTFE Grease

Super Lube Grease



LOCTITE

- Multi-purpose synthetic lubricant
- Contains PTFE for added lubricity giving superior anti-wear performance over conventional greases and oils
- Odourless, clean and non-staining
- Wax free for excellent flow at low temperatures
- Contains anti-oxidants and rust inhibitors
- Temperature range -40°C to +176°C, intermittent use to +260°C

Price Each

Order Code	Product Code	Type	1+	3+
WX45583	S/LUBE0ILX7G	Precision Oil	£5.48	£5.27
WX45580	S/LUBEAEROX357ML	Aerosol	£12.62	£12.13
WX45582	S/LUBEGREASEX85G	Tube	£7.45	£7.15
WX45581	S/LUBEGREASEX400GRM	Cartridge	£15.67	£15.08

**Need advice?
FREE technical
support at every
Brammer branch**

Cold Metal Forming Lubricants

Ultraform Range

Ultraform 1030



- Ultimate performance neat oil forming lubricant
- Suited to the most severe and demanding forming operation
- Leaves an oily film which provides excellent corrosion protection
- Easily cleaned prior to the finishing processes

Price Each

Order Code	Product Code	Size	1+	4+
WX23161 ‡	86083	20 Ltr	£211.90	£206.18

Ultraform 1050



- Low residue neat oil forming lubricant
- Light to medium duty operations
- Normally requires no cleaning prior to finishing process
- Suitable for heat degreasing where absolute cleanliness is required

Price Each

Order Code	Product Code	Size	1+	4+
WX23164 ‡	86103	20 Ltr	£232.63	£226.34

Ultraform 2030



- High performance EP forming lubricant
- Superior load carrying characteristics reduce metal pick up and scoring
- Suitable for use with carbide tooling
- Can be used neat or diluted with water or mineral oil
- Suitable for use in re-circulating systems

Price Each

Order Code	Product Code	Size	1+	4+
WX23155 ‡	86013	20 Ltr	£304.39	£296.16

Ultraform Advantage



- Chlorine-free lubricant designed for all cold metal pressing and drawing operations
- High performance giving minimal scrap
- Wide dilution range using either oil or water giving economy
- Easy to clean
- Suitable for all metals
- Difficult operations use neat
- May be applied by brush, drip or airless spray system

Price Each

Order Code	Product Code	Size	1+	4+
WX23167 ‡	86273	20 Ltr	£376.49	£366.31

‡ Special delivery applies. Please call for details

Cutting & Grinding Fluid Care

Ultraguard SC



- Machine tool system cleaner
- Specially designed for use prior to recharging machine tools with fresh cutting or grinding fluid
- Cleans and disinfects in one operation
- Prevents contamination of fresh coolant
- Dilution ration 100:1

Price Each

Order Code	Product Code	Size	1+	4+
WX23109 ‡	52024	1 Ltr	£40.04	£38.96
WX23110 ‡	52026	5 Ltr	£163.68	£159.26

‡ Special delivery applies. Please call for details

Metal Cutting & Grinding Fluids

Flood Applied Fluids

Ultracut Range



- The Ultracut range of cutting fluids have been developed to provide exceptional performance and extended tool life
- The range includes products for all metal removal operations
- Always at the forefront of technology in terms of performance as well as safety and environmental characteristics

Ultracut 250 Plus

- Long life soluble oil cutting fluid
- Light/medium cutting operations, dilute between 20:1 & 40:1 in water

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23085	51366	5 ltr	£60.67	£59.03
WX23086	51363	20 ltr	£199.04	£193.66
WX32400 ‡	51362	60 ltr	£499.54	£486.04

Ultracut 255

- Long life EP soluble cutting fluid
- Medium/severe cutting operations, dilute between 20:1 & 40:1 in water

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23081	51336	5ltr	£83.63	£81.36
WX23082 ‡	51333	20ltr	£286.31	£278.57

Ultracut 260

- Long life high performance EP soluble oil cutting fluid
- Severe cutting operations, including alloys, stainless, titanium etc
- Dilute between 20:1 & 40:1 in water

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23078	51263	20ltr	£347.56	£338.16
WX32398 ‡	51264	60ltr	£937.08	£911.76

Ultracut 280A Plus

- Long life high performance soluble oil cutting fluid for aluminium and its alloys
- Dilute between 15:1 and 25:1 in water

Order Code	Product Code	Size	Price Each	
			1+	4+
WX34103	51682	20ltr	£199.04	£193.66

Ultracut 370 Plus

- Long life high dilution semi-synthetic cutting & grinding fluid
- Light/medium cutting and grinding operations
- Forms a translucent green micro-emulsion when mixed with water, provides clear view of the workpiece
- Dilute between 40:1 and 60:1 for cutting; 50:1 and 70:1 in water for grinding

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23089	51376	5 ltr	£83.63	£81.36
WX23090	51373	20 ltr	£284.83	£277.14
WX32401	51372	60 ltr	£687.86	£669.27

‡ Special delivery applies. Please call for details

V-cut Range

V-cut MT



- Milky type water mix fluid for all general cutting operations
- Stable low foaming milky white emulsion
- High oil content ensures a high degree of residual corrosion protection on machine surfaces and workpieces
- Low odour
- Recommended operating dilution 15:1 to 20:1

Order Code	Product Code	Size	Price Each	
			1+	4+
WX42719	51516	5 ltr	£34.54	£33.54
WX23094	51513	20 ltr	£90.93	£88.29
WX32402	51514	60 ltr	£269.93	£262.10

V-cut SS

- Semi-synthetic water mix fluid for all general cutting & grinding operations
- Forms translucent green micro-emulsion in water
- Allows a clear view of the cutting zone
- Unique corrosion inhibition package extends the working dilution range and minimises in-sump cost
- Rationalise to use one fluid for cutting and grinding
- Low odour
- Recommended operating dilution: Cutting 35:1 to 45:1, Grinding 45:1 to 55:1

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23099	51523	20 Ltr	£122.46	£118.91
WX23097	51524	60 Ltr	£347.01	£336.96

V-cut EP

- Extreme pressure, high performance water mix cutting fluid
- For heavy duty cutting operations on hardened steels and other difficult to machine alloys
- Special EP additive extends tool life and improves surface finish
- Long life sump
- Stable low foaming milky white emulsion
- Low odour
- Recommended operating dilution 20:1 to 40:1

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23103	51533	20 Ltr	£134.16	£130.28
WX23101	51534	60 Ltr	£376.27	£365.36

**Can't see it here,
just call
0870 240 2100**

Hand Applied Cutting Fluids

TRI-Logic RTD



- Extends tool life
- Improves surface finish
- Reinforces water mix cutting fluids
- Resists degradation
- Easily removed by aqueous cleaners
- Low odour - pleasant to use
- Contains no silicones
- Suitable for use on CNC machines

Order Code	Product Code	Size	Price Each	
			1+	4+
WX38339	53003	350 ml	£17.24	£16.74
WX38340 ‡	53006	5 Ltr	£151.01	£146.93
WX38341 ‡	53008	20 Ltr	£518.76	£504.74

RTD Metal Cutting Liquid

- Ultimate cutting performance
- Extreme pressure additives for use in reaming, tapping, drilling and other metal cutting operations
- Significantly reduces friction giving superb cutting performance
- Flows to cutting edge
- Oil and solvent free
- Suitable for automatic application on CNC machines
- Contains no silicones

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23129	53072	400g	£17.24	£16.74
WX23130	53076	5 ltr	£151.01	£146.93
WX32404 ‡	53078	20 ltr	£518.76	£504.74

RTD Cleancut Liquid

- Sulphur & chlorine free tapping fluid
- Suitable for aerospace & nuclear applications
- Low viscosity, water soluble lubricant
- Non-fuming, low odour characteristics
- Non-staining on yellow metals & aluminium
- Improves surface finish
- Can be cut back with water - greater economy
- Compatible with water mix cutting fluids

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23125	53062	350g	£17.66	£17.14
WX23126	53066	5 ltr	£154.00	£149.84

RTD Metal Cutting Compound

- Soft low melting-point paste
- For use in reaming, tapping and drilling and other metal cutting operations
- Formulated to cling to the tool providing excellent cutting performance
- Improves surface finish
- Allows increases removal rates
- Significantly reduces friction giving superb cutting performance
- Suitable for the most severe cutting operations
- Suitable for all metals including hardened steels, nimonics and titaniums
- Apply directly to the tool or workpiece by brush, or by dipping tool into the compound

Order Code	Product Code	Size	Price Each	
			1+	4+
WX23119	53020	50g	£4.24	£4.12
WX23120	53023	500g	£11.52	£11.19
WX23121 ‡	53026	5Kg	£108.24	£105.31
WX23123 ‡	53028	18Kg	£372.99	£362.91

RTD Metal Cutting Spray

- Metal cutting lubricant which doubles tool life
- Medium viscosity liquid in an aerosol
- Suitable for severe cutting operations
- Ideal for use where accessibility is a problem
- Can be applied directly for moving tools

Price Each

Order Code	Product Code	Size	1+	6+
WX34104	53011	400ml	£17.40	£16.90

RTD Metal Cutting Foamcut

- Foaming lubricant which doubles tool life
- Clean low odour
- Foaming action ensures lubricant rapidly penetrates to the cutting edges without running off the tool or workpiece
- Allows economical application, even in deep holes
- Suitable for severe cutting operations
- Can be applied directly to moving tools

Price Each

Order Code	Product Code	Size	1+	6+
WX34105	53041	300ml	£20.70	£20.10

‡ Special delivery applies. Please call for details

Slideway Lubricants

Ultraglide X5



- Total protection slideway lubricant
- Resistant to water wash off/protects slides from corrosion
- Reduces wear and prevents 'stick slip'
- Separates rapidly from cutting fluid & easily removed by oil skimmers/separators
- Available in an aerosol for machine tools without automatic lubrication systems

Price Each

Order Code	Product Code	Size	1+	4+
WX34106	52041	400ml Aerosol	£16.81	£16.32
WX23114 ‡	52086	5 Ltr	£32.82	£31.93
WX34107 ‡	52083	20Ltr	£91.44	£88.97

‡ Special delivery applies. Please call for details

For a full range of cleaning products, see our Janitorial section



Texaco Waylube



- Exceptional wetting, adhesion and lubricity
- Minimises stick slip problems
- High load carrying qualities
- Chlorine-free formulation
- Reduces metal processing machine and slideway wear
- Approved by Cincinnati P-47 & P-50

Price Each

Order Code	Product Code	1+	4+
WX45611	WAYLUBEX68X20LTR	£77.69	£73.45
WX45610	WAYLUBEX220X20LTR	£77.69	£73.45

Spill risk minimisation services available from Fosse Licitrol. Including Site assessments, accredited training, bund relining and repairs



MECRO

Exclusively available through Brammer

The first choice for:

- absorbent pads, rolls and socks
- spill response kits
- drill sets
- cleaning and maintenance sprays
- performance and maintenance lubricants



for more information or to place an order
call 0870 240 2100 or visit www.mecro.co.uk

